

**WATER WELL RECORD (WWC-5)**

Constructed

KOLAR DOC ID 1642884

WELL ID \_\_\_\_\_

Original Record  Correction  Change in Well Use

**LOCATION OF WATER WELL**

Latitude	38.698299	Longitude	-99.413885	Section	34	Township	15	Range	19	<input type="checkbox"/> E <input checked="" type="checkbox"/> W	Fraction	SE ¼ SE ¼ SE ¼
Datum	WGS84	Elevation	2028	County	Ellis							

**WATER WELL OWNER**

Name	Clinton Werth
Business	
Address	4503 Danby Lane Hays KS 67601
Well location	Intersection of 200 Ave & Ave A North 600' & west 400'
<input type="checkbox"/> at owner's address	

**WELL WATER USE**

Domestic Household

**COMPLETION**

Depth of completed well: 420 ft.  
 Depth(s) groundwater encountered:  
 (1) \_\_\_\_\_ ft.; (2) \_\_\_\_\_ ft.;  
 (3) \_\_\_\_\_ ft.; (4)  dry well

Static water level in well: 142 ft.  
 measured below land surface on (mm/dd/yy): 04/22/2022  
 measured above land surface on (mm/dd/yy): \_\_\_\_\_

Estimated yield: 35 gpm  
 Water level was: \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ gpm

Pump installed?  Yes  No

Water well disinfected?  Yes  No  
 Date disinfected (mm/dd/yy): 04/22/2022

Aquifer, if known: \_\_\_\_\_

**NEAREST SOURCE OF POTENTIAL CONTAMINATION**

Source: Livestock pens

Distance from well: 900 Direction from well: S

Source description: Feedlot

Source: \_\_\_\_\_

Distance from well: \_\_\_\_\_ Direction from well: \_\_\_\_\_

Source description: \_\_\_\_\_

No potential source of contamination within 100 feet.

**CONSTRUCTION**

Borehole interval: from <u>0</u> to <u>420</u> ft.	Borehole diameter: <u>9</u> in.
Casing height above land surface: <u>18</u> in. If casing height is less than 12 in. has a variance been approved?* <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No *variance not required for monitoring or environmental remediation wells	
Casing type: <u>ThermalPlastic</u>	
Blank casing interval: <u>0</u> ft. to <u>360</u> ft.	
Blank casing diameter: <u>5</u> in.	
Casing joints: <u>Splines</u>	
Weight: _____ lbs/ft.	
Wall thickness or gauge no.: <u>SDR17</u>	
Blank casing interval: _____ ft. to _____ ft.	
Blank casing diameter: _____ in.	
Casing joints: _____	
Weight: _____ lbs/ft.	
Wall thickness or gauge no.: _____	
Grout interval: <u>5</u> ft. to <u>60</u> ft.	
Grout material: <u>Bentonite</u>	
Grout interval: _____ ft. to _____ ft.	
Grout material: _____	
Screen / perforation material: <u>PVC</u>	
Screen / perforation openings: <u>Saw cut</u>	
Screen / perforation intervals: From <u>360</u> ft. to <u>420</u> ft. Slot size <u>32</u> unit <u>millimet</u>	
From _____ ft. to _____ ft. Slot size _____ unit _____	
Gravel pack intervals: Gravel pack not used: <input type="checkbox"/> Gravel size _____ in From <u>0</u> ft. to <u>5</u> ft.	
Gravel pack not used: <input type="checkbox"/> Gravel size _____ in From <u>60</u> ft. to <u>420</u> ft.	

**LITHOLOGIC LOG**

FROM	TO	LITHOLOGY INTERVALS
Attach	Attach	Attached

**COMMENTS**

**CONTRACTOR'S OR LANDOWNERS CERTIFICATION**

This water well was constructed  reconstructed  pursuant to the stated water well contractor's license and was completed on 04/22/2022. I certify that this record is true to the best of my knowledge and belief. This water well record was completed on \_\_\_\_\_ under the business name of Nash Water Well Service, LLC, Kansas Water Well Contractor's License No. 846 under the authority of the designated person as defined in K.A.R. 28-30-2(j) and signed and certified by the electronic signature of the designated person at its submittal: Trevor Nash.

Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.

Form	WWC5.2 - Water Well Record
Doc ID	1642884
Well Owner	Clinton Werth
Contractor	Nash Water Well Service, LLC

Lithology

From	To	Lithology Intervals
0	3	,top soil
3	28	,tan yellow clay with rock streaks and layers
28	205	,blue shal with rock streaks and layers
205	215	,white gray clay
215	225	,gray clay
225	229	,tan clay
229	245	,gray white clay with thin sandstone streaks
245	259	,brown clay
259	265	,red clay
265	285	,tan gray red clay
285	300	,brown gray clay
300	320	,gray clay with thin sandstone streaks
320	332	,gray clay
332	350	,blue gray clay/shale with thin sandstone streaks
350	352	,red clay
352	360	,gray sandstone with gray clay
360	380	,gray sandstone
380	400	,gray clay with gray sandstone
400	420	,blue shale