

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		SW 1/4 SW 1/4 NE 1/4	35	T 15 S	R 2 E/W
Distance and direction from nearest town or city street address of well if located within city? 1/2 MILE SOUTH 4 1/2 WEST OF GYPSUM, KS.					
2 WATER WELL OWNER: PIONEER LAKE ASSO. RR#, St. Address, Box # : 415 HART City, State, ZIP Code : SALINA, KS. 67401					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION: 1290			
<div style="text-align: center;">N +-----+   NW   NE   +-----+   X        +-----+ S W                  E</div>		Depth(s) Groundwater Encountered 1. 16 ft. 2.     ft. 3.     ft.			
		WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 2-11-91			
		Pump test data: Well water was 25 ft. after 1 hours pumping 25 gpm			
		Est. Yield 50 gpm: Well water was     ft. after     hours pumping     gpm			
		Bore Hole Diameter 9 in. to 43 ft., and     in. to     ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 23 ft., Dia     in. to     ft., Dia     in. to     ft. Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot .) # .035 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 29 ft. to 43 ft., From     ft. to     ft. GRAVEL PACK INTERVALS: From 20 ft. to 43 ft., From     ft. to     ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 3/8 4 Other Grout Intervals: From 0 ft. to 20 ft., From     ft. to     ft., From     ft. to     ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? NORTH WEST How many feet? 50					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 16 CLAY BROWN					
16 25 FINE WHITE SAND					
25 36 RED SAND STONE					
36 43 TAN SAND STONE WITH ROCK LAYERS					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-12-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 2-12-91 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					