


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Saline	SW 1/4 SW 1/4 NW 1/4	36	T 15 S	R 2

Distance and direction from nearest town or city street address of well if located within city?

4 Miles West of Gypsum, KS

2 WATER WELL OWNER: City of Gypsum	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: City Hall	Application Number: #8722
City, State, ZIP Code: Gypsum, KS 67448	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 46'1" ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 46'1" ft. below land surface measured on mo/day/yr 11/1/90
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 50 gpm: Well water was 70 ft. after 8 hours pumping 50 gpm
	Bore Hole Diameter 10 in. to 82 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes X No; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 6 in. to 70 ft., Dia			11 Other (specify)
Casing height above land surface 12 in., weight 3.36 lbs./ft. Wall thickness or gauge No. 255			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	
1 Steel	3 Stainless steel	9 ABS	
2 Brass	4 Galvanized steel	10 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 25 ft. to 80 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 5 ft. to 25 ft., From ft. to ft.				
What is the nearest source of possible contamination: None within 1/2 mile				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	5	Red Clay			
5	14	Red Sandstone			
14	17	Gray Clay			
17	25	Brown Sandstone			
25	36	Red Sandstone			
36	37	Gray Shale			
37	48	Dark Red Sandstone			
48	81	Light Brown Sandstone			
81	82	Iron Pirite			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-23-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 1-2-91 under the business name of Peterson Irrigation Inc. by (signature) Mike Peterson
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.