

CORRECTION(S) TO WATER WELL RECORD (WWC-5)  
(to rectify lacking or incorrect information)

Location listed as:

Section-Township-Range: 36-15S-22W

Fraction ( 1/4 1/4 1/4): NW NE NW

County: Trego

Location changed to:

36-15S-22W

NW NW NE NW

Other changes: Initial statements: Ness County

Changed to: Trego County

Comments:

verification method: Latitude and Longitude, KGS' "LEO" conversion tool, other KSU monitoring wells nearby, and mapping tool & aerial photos on KGS website. initials: DRJ date: 5/2/2011

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

46-068-10517

WATER WELL RECORD

Form WWC-5


Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NW 1/4 Section Number 36 Township Number T 15 S Range Number R 22 W

Distance and direction from nearest town or city street address of well if located within city? RR#1, Box 28, Brownell, KS

2 WATER WELL OWNER: David Weaver / KSU Foundation RR#, St. Address, Box # : 2323 Anderson, Suite 500 City, State, ZIP Code : Manhattan, KS 66502

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 82.5 ft.

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 58.18 ft. below land surface measured on mo/day/yr 3/17/11

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass

Blank casing diameter 2 in. to 62.5 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.30 ft., Weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 62.5 ft. to 82.5 ft. GRAVEL PACK INTERVALS: From 58.6 ft. to 85 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1 ft Grout Intervals From 1 ft. to 58.6 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well

Direction from well? SW How many feet? ~114 ft

Table with columns FROM, TO, LITHOLOGIC LOG. Rows include Topsoil, Brown clay, Brown silty clay, White hard siliceous deposit, Grayish white limestone, Fine-med, red brown-tan sand w/ white hard siliceous deposit, Coarse sand, Coarse sand, well rounded-angular limestone fragments, chert, variegated, coarser w/ depth, Flushmount waiver from BOW.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/16/11 and this record is true to the best of my knowledge and belief.

INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.