Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | | | | | | | . , | | |
|--|-------------------------------------|---------------------------------------|-------|----------------|---------------------------------|--|---------------------------------|-------------------|--|
| 1. Location of well: | County | Fraction SW 1/4 SW 1/4 SE 1/4 | | Section number | | Township number | Range number | | |
| 1. LOCUITOR OF WELL: | Gove | | | | | T 15 | s R 29 | ₽ | |
| 2. Distance and direction from nearest town or city: 9N, 2½E of | | | | | : | York Bros. | | | |
| Street address of well location if in city: Healy, Kansas R.R. or s City, sta | | | | | rate, zip code: Healy, KS 67850 | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia. 26 in. Completion date Well depth 55 ft. 4-16-77 | | | |
| N | | | Xu | IELL | | | | | |
| | - NF | / | | | | 7 Cable tool Rotar Hollow rod Jette | yDrivenDug dBored —XRev | g verse rotary | |
| • | 1 | 1/2 | | 10 | | 8. Use: Domestic | | | |
| w | E E | 1 | ן ימי | | | X Irrigation | Air conditioning S | itock Other | |
| sw | SE TG | | | | | Asbestos Cemen 9. Casing: Material Bandea | Height: boyer | | |
| | SEPTIC | | | | | | -iSurface - 10 | in. | |
| S 1 —— 1 Mi | ile | | | | | PVC Dia. 16 in. to 55 ft. de | | lbs./ft. | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. depth gage No7/8 | | | |
| | | | | | | 10. Screen: Manufacturer's name Johnson & Cook | | | |
| Clay | | | | | 6 | Type Steel Dia. 16 in. | | | |
| Sand | | | | | 18 | Set between | | | |
| | | | | | | ft. andft. | | | |
| Sd clay strs | | | | | 22_ | 11 Static water levels me /day/yr | | | |
| Sand | | | | 22 | 53 | 11. Static water level: mo./day/yr. 8 ft. below land surface Date 4-7-77 | | | |
| Shale | | | | 53 | 55 | 12. Fumping level below land surfaces: 26 ft. after 8 hrs. pumping 800 g.p.m. | | | |
| | | | | | | ft. after | hrs. pumping | g.p.m. | |
| | BROOK | 53' | | | | Estimated maximum yield | 800 | g.p.m. | |
| | 171000 | | | | | 13. Water sample submitted Yes X No | Date | o./day/yr. | |
| | | | | | | 14. Well head completion: | | | |
| | | | | | | Pitless adapter | Inches above | grade | |
| | | | | | | 15. Well grouted? Yes With: X Neat cement | Bentonite | Concrete | |
| | | | | + | | Depth: From ft. to | | | |
| | | | | | | 14. Nearest source of possible ft 10560 Direction | le contamination: SW Type Se | ptic | |
| | | | | | | Well disinfected upon comp | | No | |
| | | | | | | 17. Pump: Manufacturer's name | Not installed orthington | ~ | |
| | | | | | | Model number | HP Vo | olts | |
| | | | | - | | Length of drop pipe | ft. capacity <u>80</u> | <u>/Ug.p.m.</u> | |
| | | | | | | Submersible | _X Turbin | | |
| | (Use a second sh | neet if needed) | | | | Jet Centrifugal | Recip Other | rocating & | |
| 18. Elevation: | 19. Remarks: | · · · · · · · · · · · · · · · · · · · | | <u> </u> | | 20. Water well contractor's | certification: | ^ ^ | |
| | | | | | | This well was drilled under | , , | is report | |
| Topography: | | | | | | is true to the best of my kno Weishaar Dri | - | 232 🕏 | |
| Hill Slope | | | | | | Business name | tv/ks 6787 | cense No. | |
| Upland | | | | | | Signatural | lander | | |
| Valley | | | | | | Authorized re | presentative 6-7- | <u>.77</u> ₹ | |
| prward the white, blue | e and pink copies to the Department | of Health and Environment | | | | V | Form W | wc-5 | |