			L RECORD Form W		82a-1212	T	Donas Nambas
1 LOCATION OF WATE	R WELL:	Fraction SE 1/4	CW CW	1	n Number 17	1 4-	Range Number
Distance and direction from ne	line	ity street address (of well if located within		17	1 10	
Smolan Oil, 402 E. North			, wom in 10001.00 11.1	,			
2 WATER WELL OWNE							
RR#, St. Address, Box # :						Board of Agriculture	re, Division of Water Resources
City State 7ID Code	Smolan	Ke 67456		MW-11	₹	Application Numbe	ar-
2 LOCATE WELL'S LOC	CATON WITH	4		0.5			ft. 3 ft. 5
AN "X" IN SECTION E	OX:	DEPTH OF CO	MPLETED WELL	25	. ft. ELE	VATION:	
N		• • •					
A	j	WELL'S STATIC V	NATER LEVEL 1	6.45 ft. b	elow land s	surface measured on m	io/day/yr
ww	NE	Pump t	test data: Well water	was		ft. after h	nours pumpinggpm _
		Est. Yield	gpm: Well water	was		ft. after h	nours pumpinggpm gpm gpm
₹ w 	ᆘ	Bore Hole Diamete	er 8 in. to	25		ft. and	in. to ft. 11 Injection well 12 Other (Specify below)
, i		WELL WATER TO	BE USED AS: 5 P	ublic water sup	ply	8 Air conditioning	11 Injection well
sw	SE	1 Domestic	3 Feed lot 6 C	TI TIEKO Water SU	ippiy	9 Dewatening	12 Other (Specify below)
↓ x 	i I i						
' <u> </u>	· · · · · · · · · · · · · · · · · · ·	Was a chemical/ba	acteriological sample s	submitted to De			If yes, mo/day/yr sample was
		submitted			Wa		Yes No X
5 TYPE OF BLANK CA			5 Wrought Iron	8 Concrete	e tile		Glued Clamped
1 Steel	3 RMP (S	SR)	6 Asbestos-Cement	9 Other (s	pecify belo	w)	Welded
2 PVC	4 ABS		7 Fiberglass				Threaded X
Blank casing diameter	2	in. to 10	ft., Dia	in. to		ft., Dia	in. to ft.
Casing height above land surf	ace	0 ir	n., weight	.716	lbs./ft	Wall thickness or gaug	ne No154
TYPE OF SCREEN OR PERF	ORATION MAT	TERIAL:		7 P	VC	10 Asbestos	s-cement
1 Steel			5 Fiberglass	8 R	MP (SR)		pecify)
2 Brass	4 Galvani	ized steel	6 Concrete tile	9 A	BS	12 None use	ed (open hole)
SCREEN OR PERFORATION						8 Saw cut	11 None (open hole)
1 Continuous slot	3 N	Mill slot		wrapped		9 Drilled holes	,
2 Louvered shutte		Key punched	7 Torch			10 Other (specify)	
SCREEN-PERFORATED INT	ERVALS:	From	10 ft. to	25	ft. (From	ft. to ft.
		From	ft. to		ft. I	From	ft. to ft.
GRAVEL PACK INTE	RVALS:	From	8 ft. to	25	ft. I	From	ft. to ft.
						From	
6 GROUT MATERIAL	1 Neat ce		Cement grout	3 Bento	nite	4 Other	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 2 ft. to 8 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of			ונ. רוטווו	II. 10			π. το π. 14 Abandoned water well
1 Septic tank	•		7 Pit privy				15 Oil well/ Gas well
							16 Other (specify below)
3 Watertight sewe		6 Seepage pit	9 Feedyar			ticide storage	Contaminated site
Direction from well? How many feet?							
FROM TO	CODE	LITHOLO	OGIC LOG	FROM	то		SING INTERVALS
0 1	gra						
1 3.5		y clay					
3.5 7		y clay					
7 13		yey silt	14	-			
13 19 19 23		yey sandy si yey sand, w/o					
23 25		nse sandy cla					
20 20	1081	ioe earlug cle	<u>-j</u>				
	 			1			
7 CONTRACTOR'S OR	LANDOWNER'			s (1) construct	ed, (2) rec	onstructed, or (3) plugg	ed under my jurisdiction and was
completed on (mo/day/yr)		11-13		and this	record is t	rue to the best of my kn	nowledge and belief. Kansas
Water Well Contractor's Licen	se No.		554	This Wa	ter Well Re	ecord was completed or	n (mo/day/yr) 020504
under the business name of		Woofter	Pump and Well	inc.	b	y (signature)	sun Cole Valle
INSTRUCTIONS: Please	fill in blanks and c	circle the correct ans	wers. Send three copies	s to Kansas Dep	artment of h	lealth and Environment,	dreau of Water, Topeka, Kansas
66620-0001. Telephone: 9	13-280-3545. Se	SHU ONE TO WATER	AAETT CAAMER SUG LGES	an one for your n	JUIUS.		