			WATER	WELL RECORD	Form WWC-5	KSA 82a-1212				
1 LOCATION OF WATER WELL:			Fraction		Section Number	Township	Number Range Number		r	
County: Saline		NW 1/4 NE 1/4 SW 1/4		19 T 15		S R 3		E(W)		
Distance and direc	tion from near	est towr	or city stree	t address of well if loca	ated within city?					
1 mile SW of S	Smolan, KS									
2 WATER WEL	L OWNER:	Morris	on Venture	es						
RR#, St. Address,	Box#:	1700 E	East Iron			Board of Agric	ułture, Divisio	on of Water Resou	rces	
City, State, ZIP Co	ode :	Salina	, KS 6740	1		Application Nu	mber:		ĺ	
		N WITH	4 DEPTH	OF COMPLETED WE	LL55 ft.	ELEVATION				
N "X" IN SECTIO				oundwater Encountere						
	N			ATIC WATER LEVEL.						
	 	1					-	-	, l	
	'		Fet Viold	Pump test data: Well water wasft. after hours pumping gpm Est. Yield: gpm: Well water wasft. after hours pumping gpm						
NM	- NE	1	1	Bore Hole Diameter3.5in. to55 ft., and in. to ft.						
w		lΕ	WELL WATER TO BE USED AS: 5 Public Water supply 8 Air conditioning 11 Injection well							
AA IX		75	1				•	•		
-010/	, ,	1			Oil field water supp	_	-			
-sw		1	2 Irrigation		Lawn and garden o				1	
i	<u> </u>	_	1	nical/bacteriological sa				-	//yr	
	S		sample was	submitted		Water well dis	sinfected? Ye	s NoX		
5 TYPE OF BLA	NK CASING	USED:	5 Wrought	Iron	8 Concrete tile		CASING JOINTS: GluedClamped			
1 Steel	3 RMP (SR)		6 Asbestos	-Cement	9 Other (specify b	pelow)		Welded		
(2)PVC	4 ABS		7 Fiberglas	S				Threaded	x	
\sim	eter1 ir	n. to4	•	in. to	ft., Dia	in. to	ft.		j	
				, weight				CH 40		
YPE OF SCREE					7)•vc	10 Asbestos-c	-	, , , , , , , , , , , , , , , , , , ,		
	3 Stainless st		* WOY! LINDYL	5 Fiberglass	8 RMP (SR)	11 Other (spec				
				•	•		• /			
	4 Galvanized		00.455	Concrete tile	9 ABS	12 None used				
CREEN OR PER				5 Gauze wrapped	8 Saw cut		11 None (ope	en hole)		
1 Continuous sl	,	3)Mill sl		6 Wire wrapped	9 Drilled holes					
2 Louvered shu		4 Key p	unched	7 Torch cut	10 Other (specify	•				
SCREEN PERFO	RATED INTER	RVALS:		From40ft		•				
				Fromft.						
GRAVEL PAC	CK INTERVAL	S:		From39ft.	. to ft	., From	ft. to	ft.		
				Fromft.	to ft.	, From	ft. to	ft.		
6 GROUT MA	TERIAL:	1 Neat	cement	2 Cement grout	(3)Bentonite	4 Other				
Grout Intervals:	From0	ft. to	39 f	t., From ft.	To ft., From	ft. t	o fi	t.		
What is the neare:	st source of po	ssible c	ontamination	1:	10 Livestock pen	S	14 Abandone	ed water well		
1 Septic tank 4 Lateral lines				7 Pit privy	11 Fuel storage					
2 Sewer lines 5 Cess po										
3 Watertight s		6 Seepa		9 Feedyard	13 Insecticide sto	-	To Other (Sp.	cony below,		
Direction from wel		О Осср	age pit	3 i ecuyalu	How many feet?	nage	•••••			
			LITTIO	0010100	· · · · · · · · · · · · · · · · · · ·	TO 1	DILLIC	OINO INTERVALO		
FROM	TO		LITHOL	OGIC LOG	FROM	ТО		GING INTERVALS		
0	=	Clay			39.5		Clay			
3		Silt			43		Gravel			
5		Clay			43.5	50	Clay			
12	14.5	Silt			50	52	Sand			
14.5	15	Sand			52	55	Clay			
15	19.5	Clay								
19.5	24.5	_								
24.5		Sand			1	1				
29.5		Clay			_	 				
29.5	1				-	 			-	
		Sand			 	 				
31		Clay			-		1044.00			
35.5		Sand				<u> </u>	MW-23d			
				CATION: This water w					у	
				7/2/08 a						
Kansas Water We	ell Contractor's	License	e No709	This Water W	ell Record was com	pleted on (mo/	day/yr)7/	9,08		
under the busines					by (signature)	1 hours	· Val	~ ()		
				ASE PRESS FIRMLY and		fill in blanks, und	lerline or circle	e correct answers.		
				and Environment, Bureau o		•	•			
	ATER WELL ON	-				00000 0001.	. Siepilolie, oli			