WATER WELL RECORD Form WWC-5					Division of Water Resources App. No.		
	ATION ty: Sali	OF WATER WELL:	Fraction SE 1/4 NE 1/4 NE 1/2	4 SE 1/4		Range Number R 3 □E ☑W	
		ddress of Well Location;	Global Positioning System (GPS) inf				
from	nearest t	own or intersection: If at o	owner's address, check he	Latitude: .38.72255 (in decimal degrees)			
	Approximately 3100 ft. south of the intersection of Burma Road and Smolan Road.			Longitude: 97.6855 (in decimal degrees) Elevation: □ Datum: ✓ WGS 84, □ NAD 83, □ NAD 27			
				Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Morrison Ventures RR#, Street Address, Box #: 1700 East Iron			Collection Method: ☐ GPS unit (Make/Model: Garmin GPSMAP)				
City, State, ZIP Code : Salina, KS 67401			☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey				
	, ,	Saliria, i	NS 07401		Est. Accuracy:	5-15 m, □>15 m	
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .55							
	H AN "X" IN 4 DEPTH OF COMPLETED WELL .99						
SECI	N WELL'S STATIC WATER LEVEL 18.7 ft. below land surface measured on mo/day/yr						
	Pump test data: Well water wasft. after hours pumping gpm						
,	EST. YIELDgpm. Well water wasft. after hours pumping						
W E Bore Hole Diameter 3.42in. to .52ft., andin. toft.							
 	WELL WATER TO BE USED AS:						
swse Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well							
S If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected? Yes No							
5 TYPE OF CASING USED: Steel V PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .1 in. to .55 ft., Diameter in. to ft., Diameter ft.							
Casing height above land surface. 43 in., Weightlbs./ft., Wall thickness or gauge NoSCH.40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel							
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
From							
6 GROUT MATERIAL: Neat cement Cement grout Dentonite Other							
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other							
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well VOC contamination							
Direc	ction from	n well			rom well Monitoring.wellMW-29.		
FROM	ТО	LITHOLOG	IC LOG	FROM	TO LITHO. LOG (cont.) or PLUG	GGING INTERVALS	
0	2	topsoil			4	A Printer.	
41	41	clay					
44	46	silty clay clay					
46	55	silty clay					
-,0		J					
		A CONTRACTOR OF THE CONTRACTOR					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\begin{align*} \text{constructed}, \text{reconstructed}, \text{or } \text{plugged} \\ pl							
under my jurisdiction and was completed on (mo/day/year) .2/6/12							
under the business name of Plains Environmental Services, Inc. by (signature)							
INSTRUCTIONS: Use ty pewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed, well. Vi sit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							