


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SALINE		SW 1/4 SE 1/4 SW 1/4	1	T 15 S	R 3 E/W
Distance and direction from nearest town or city street address of well if located within city? 1 MILE SOUTH OF SALINA, KS. ON HWY 81					
2 WATER WELL OWNER: WESTERN AUTO DISTRIBUTION CENTER		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: P.O. BOX 1580		Application Number:			
City, State, ZIP Code: SALINA, KS. 67401					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 1248			
<div style="text-align: center;"></div>		Depth(s) Groundwater Encountered 1. 22 ft. 2. 22 ft. 3. 22 ft.			
		WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 9-16-92			
		Pump test data: Well water was 23 1/2 ft. after 1 hours pumping 25 gpm			
		Est. Yield 100 gpm: Well water was 23 1/2 ft. after 1 hours pumping 25 gpm			
		Bore Hole Diameter 9 in. to 60 ft., and 60 in. to 60 ft.			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/>			
1 Steel		5 Wrought iron	8 Concrete tile	Welded <input type="checkbox"/>	
2 PVC		3 RMP (SR)	9 Other (specify below)	Threaded <input type="checkbox"/>	
3 RMP (SR)		6 Asbestos-Cement			
4 ABS		7 Fiberglass			
Blank casing diameter 5 in. to 50 ft., Dia 50 in. to 50 ft., Dia 50 in. to 50 ft.					
Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot		3 Mill slot .035	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft., From 50 ft. to 60 ft., From 50 ft. to 60 ft.					
GRAVEL PACK INTERVALS: From 35 ft. to 60 ft., From 35 ft. to 60 ft., From 35 ft. to 60 ft.					
6 GROUT MATERIAL:		3 Bentonite			
1 Neat cement		2 Cement grout	4 Other		
Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 60 ft., From 20 ft. to 60 ft.					
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well?		NONE APPARENT			
How many feet?					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	2	TOP SOIL			
2	18	CLAY BROWN			
18	28	CLAY RED SILTY			
28	49	SAND FINE			
49	49.5	CLAY GRAY			
49.5	60	SAND MED. TO COARSE			
		SHALE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-21-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 9-21-92 under the business name of PESTINGER PUMP SERVICE by (signature) <i>Paul Pestinger</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					