

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Saline		NE 1/4 NE 1/4 NW 1/4		3		T 15 S		R 3 E	
Distance and direction from nearest town or city street address of well if located within city? 3119 Arnold, Salina, Kansas									
2 WATER WELL OWNER: Pony Express Courier Corp. RR#, St. Address, Box #: Bldg 217, 3119 Arnold City, State, ZIP Code: Salina, Kansas 67401									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 									
4 DEPTH OF COMPLETED WELL: 13 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 6 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 5.48 ft. below land surface measured on mo/day/yr 6-14-91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7.5/8 in. to 13 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 3 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 0 in. weight lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot .010 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 13 ft. to 3 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 13 ft. to 2.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 2.5 ft. to 1 ft. From ft. to 0 (cement) ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? E-SE How many feet? 30 10 Underground fuel storage site									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 .5 Asphalt .5 3 Fill - coarse sand 3 8 Clay - silty, dk. gray 8 10 Clay - silty, dk. brown 10 13 Clay - silty, sandy, v.f., brown Completed at the surface with a bolt down steel protective manhole cover set in concrete. Well sealed with a watertight expandable locking cap.									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-7-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 6-18-91 under the business name of GeoCore Services, Inc. by (signature) Dab G. Galt									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									