

2-inch SDR 26 PVC cased to 70 ft., lower 3 ft. 0.040 " slots.
Gravel pack 65-72, Bentonite pellets 63 to 65, Gravel 20-63,
Bentonite Holeplug 0-20.

Static water level, 15.74 ft. below top of casing 1.6 ft.
above land surface 11/08/88

No. 88-14, SW SE SW Sec. 7, 23.5 ft, S-SE of No. 88-12. Observation well

Alluvium:

0	6	Clay, silty, dark and light gray
6	26	Clay, silty, light brown
26	27	Sand, fine to medium, gravel, fine to coarse, silty.
27	36	Clay, light gray and light brown
36	38	Sand, fine to medium, gravel, fine to coarse and clay, light gray. Low permeability.
38	42	Clay, light gray and light gray-brown, some sandstone rubble

4-inch SDR 26 PVC cased to 39 ft. Lower 3 ft. 0.040" slot screen.
Gravel-packed 35-39, Bentonite pellets 33-35, gravel, 20-33,
bentonite Holeplug 0 to 20

Static water level, 15.80 below top of casing 1.5 ft.
above land surface 11/08/88

No. 88-15, SE SE SW Sec. 7, 22 ft. S-SE of No. 88-13, 35.5 Ft. east of No. 88-14.
Observation well.

Alluvium:

0	6	Clay, silty, dark and light gray
6	22	Clay, silty, light brown
22	26	Sand fine to medium and gravel, fine to coarse
26	29	Clay, light gray and brown
29	34	Sand, fine to medium, gravel, fine to coarse and clay, light gray
34	65	Clay, silty, light brown, sporadic pebbles of sandstone.
65	67	Sand, fine to medium and gravel, coarse to fine, silty

Permian:

67	68	Shale, red-brown
----	----	------------------

4-inch SDR 26 PVC cased to 68 ft. 0.040" slot screen 65-68.
Gravel-packed 63-68. Bentonite pellets 61 to 63. Gravel 20 to 61.
Holeplug bentonite 0-20

Static water level 16.0 ft. below top of casing 2 ft. above
land surface 11/08/88