			WA	TER WELL RECORD	Form WV	NC-5 K	SA 82a			
LOCATIO	ON OF WATE	R WELL:	Fraction		_	Section N	lumber	[Number	Range Number
County:			SW	1/4 NW 1/4 SE		3		<u> </u>	<u>15 s</u>	R 3 E(W')
			•	t address of well if locate	a within c	my?				
			al and Wall							
			l Airport Au	ulority				Board o	of Agriculture.	Division of Water Resources
RR#, St. Address, Box # : 3237 Armold Ave. City, State, ZIP Code : Salina, Kansas 67401						Application Number:				
LOCATE	WELL'S LO	CATION WITH	A DEPTH OF	COMPLETED WELL	20		FLEVA			
AN "X"	IN SECTION	BOX:	Depth(s) Grou	indwater Encountered 1	dry		ft. 2	2	ft, :	3
. r	$\frac{N}{1}$		WELL'S STAT	TIC WATER LEVEL	dry	ft. below		measured	on mo/day/yr	08-09-94
1	i		Pu	imp test data: Well water	er was		ft. a	ifter	hours p	umping gpm
	- NW -	- NE	Est. Yield	gpm. Well water	er was		ft. a	ifter	hours p	umping gpm
<u>•</u>	<u>i 1</u>		Bore Hole Dia	meter75/8in. to						n. to
* w	! !	! `	WELL WATER	R TO BE USED AS:	5 Public	water supp		8 Air condition		
ī -	- sw	(- SE	1 Domes		6 Oil field	d water su	pply /	9 Dewatering	12	Other (Specify below)
	i i	•	2 Irrigatio	n 4 Industrial	7 Lawn a	and garden	only (Monitoring	well	
Į L			i .	al/bacteriological sample	submitted	to Departm		esNo Iter Well Disinfe		s, mo/day/yr sample was sub No X
5 TVPE C	JE BI VVIK CA	ASING USED:	mitted	5 Wrought iron	8 C	oncrete tile				ed Clamped
ع ۱۳۳۵ 1 Ste		3 RMP (S	(R)	6 Asbestos-Cement		Other (speci				ded
(2)PV		4 ABS	,	7 Fiberglass			-		Thre	eadedX
		2	.in. to	J						. in. to ft.
Casing hei	ght above lar	nd surface	+30	in., weight		<u>.</u>	lbs.	ft. Wall thickne	ss or gauge I	vo sch. 40
TYPE OF	SCREEN OR	PERFORATIO	N MATERIAL:		(7	Z)PVC			Asbestos-cem	
1 Ste	eel	3 Stainles	s steel	5 Fiberglass		B RMP (SF	₹))
2 Brass 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE:				6 Concrete tile					None used (o	•
		_			5 Gauzed wrapped			8 Saw cut 9 Drilled hol		11 None (open hole)
	ntinuous slot uvered shutte		Mill slot Key punched		wrapped					
) INTERVALS:					ft Fro			toft.
00,122,11	2.11 0.11.12	3 111727117120								toft.
G	RAVEL PAC	K INTERVALS								toft.
-			From					m	ft.	to ft.
	MATERIAL:		cement	(2)Cement grout	_ (3)E	Bentonite	4			
					6					ft. to
_		•	contamination:					•		Abandoned water well
1 Septic tank 4 Lateral lines (2)Sewer lines 5 Cess pool				7 Pit privy		. •			Oil well/Gas well Other (specify below)	
_		s Ces: r lines 6 See _l		8 Sewage lag 9 Feedyard	ЮОП			lizer storage cticide storage	10	Other (specify below)
Direction for	-	East	page pit	5 reedyard				inv feet?	800	
FROM	TO		LITHOLOG	IC LOG	FRO			ary roct:	PLUGGING	INTERVALS
00	8	Clay, mo		stiff, med plst						
		damp								
8	16			tiff, med plst, dam						
16	19			mod gn/gy, tr - mo	<u>d </u>					
	-		l, sl lamin							
19	20	Shale, I	t gn, tr ca	IC CISTS						,
	l 							MW2 -	Above Grad	te Cover
									TWOVE GIVE	20 00101
	<u> </u>									
	l	# # # 140 AM - 1 M				l				
7 CONTR	RACTOR'S O	R LANDOWNE		ATION: This water well v	vas((1)) co	onstructed,	(2) rec	onstructed, or (3) plugged ur	nder my jurisdiction and was
		rear)								nowledge and belief. Kansas 3-16-94
ł			527		Vell Reco			/ 1	\int_{0}^{∞}), 49, 77
	business nam		eoCore Servi		None 60 to 1		y (signa		ers and ton thre	A Opies to Kansas Department
INSTRU	JCTIONS: Use typ	pewriter or ball poin ant. Bureau of Wate	it pen. <i>PLEASE PRE</i> er. Topeka, Kansas	SS FIRMLY and PRINT clearly. F	riease till in b -5545. Send	one to WATE	R WELL (DWNER and retain	one for your reco	rds.