

[1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Saline		NW ¼ NW ¼ SW ¼ E	7	T 15 S	R 3 EW
Distance and direction from nearest town or city street address of well if located within city? <div align="center">Salina Landfill</div>					
[2] WATER WELL OWNER: City of Salina RR#, St Address, Box #: 300 W. Ash Board of Agriculture, Division of Water Resources City, State, ZIP Code : Salina, Kansas 67401 Application Number:					
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		[4] DEPTH OF COMPLETED WELL 24.5 ft. ELEVATION: 1324			
<p>A map of a quarter-section grid divided into four quadrants by dashed lines. The top-left quadrant is labeled 'NW', top-right 'NE', bottom-left 'SW', and bottom-right 'SE'. A small 'X' is drawn in the center of the NW quadrant.</p>		Depth(s) Groundwater Encountered 1.....ft 2.....ft 3.....ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 24.5 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Piezometer			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>			
[5] TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
(2) PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
		7 Fiberglass		Threaded. <u>X</u> .	
Blank casing diameter 2 in. to 10 ft., Dia					
Casing height above land surface 30 in., weight lbs./ft. Wall thickness or gauge No. sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel		5 Fiberglass		(7) PVC 10 Asbestos-cement	
2 Brass 4 Galvanized steel		6 Concrete tile		8 RMP (SR) 11 Other (specify)	
				9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot (3) Mill slot		5 Gauzed wrapped		8 Saw cut 11 None (open hole)	
2 Louvered shutter 4 Key punched		6 Wire wrapped		9 Drilled holes	
		7 Torch cut		10 Other (specify)	
SCREEN-PERFORATED INTERVALS:					
From 10 ft. to 25 ft., From ft. to ft.					
GRAVEL PACK INTERVALS:					
From 8 ft. to 25 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
[6] GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite 4 Other					
Grout Intervals: From 0 ft. to 6 ft., From 6 ft. to 8 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines		7 Pit privy		10 Livestock pens 14 Abandoned water well	
2 Sewer lines 5 Cass pool		8 Sewage lagoon		11 Fuel storage 15 Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit		9 Feedyard		12 Fertilizer storage (16) Other (specify below)	
				Landfill	
Direction from well? East				How many feet? 1000	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	cly, w/ snd			
7	15	Cly,v stiff, yell-brn, sndy, blk org oxidation 3-4" stringers			
15	17	Clay, lt brn to brn to gry			
17	24.5	Cly, softer yell-brn, v sndy, v f grvl			
					P5 - Aboveground
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09-20-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 11-16-94 under the business name of GebCore Services, Inc. by signature _____					