

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Logan Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 12 Township Number: T 15 S Range Number: R 34 EW

Distance and direction from nearest town or city street address of well if located within city? 9 miles South 3/4 miles East of Russell Springs, Kansas

2 WATER WELL OWNER: Marvin Eitel RR#, St. Address, Box #: 1211 Hillside Drive City, State, ZIP Code: Scott City, Kansas 67871 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram showing a 2x2 grid with quadrants NW, NE, SW, SE. An 'X' is marked in the NE quadrant.] 4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 35 ft. below land surface measured on 8/16/83. WELL'S STATIC WATER LEVEL: 35 ft. below land surface measured on 8/16/83. Pump test data: Well water was 44 ft. after 4 hours pumping 10 gpm. Est. Yield: 10 gpm. Well water was ft. after hours pumping gpm. Bore Hole Diameter: 9 in. to 50 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 11 Injection well, 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Observation well, Stockwell. Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below) CASING JOINTS: Glued, Clamped, Welded, Threaded.

Blank casing diameter: 5 in. to 35 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., weight: 2.9 lbs./ft. Wall thickness or gauge No. 265

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 35 ft. to 50 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 30 ft. to 50 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other Drill cuttings. Grout Intervals: From 15 ft. to 30 ft., From 4 ft. to 15 ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below)

Direction from well? South How many feet? 300

Table with 4 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHOLOGIC LOG. Row 1: FROM 0 TO 33 Clay; FROM 33 TO 44 Sand clay streaks; FROM 44 TO 50 Shale.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/20/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 232 This Water Well Record was completed on (mo/day/yr) 9/29/83 under the business name of Weishear Drilling & Supply Inc. by (signature) [Handwritten Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T 15 R

34

SEC.

12 NE 1/4 NE 1/4 NE 1/4

DP