

USE TYPEWRITER OR BALL POINT PEN—PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment—Division of Environment (Water well Contractors)
Topeka, Kansas 66620

CCC

1. Location of well: County WALLACE Fraction SW 1/4 W 1/4 1/4 Section number 29 Township number T 15 S Range number R 38 W

2. Distance and direction from nearest town or city: 1 1/2 S 1 E 3. Owner of well: Russell UNRUH
Street address of well location if in city: WALLACE, KANS. City, state, zip code: SHROANS SPRING, KANS. 67738

4. Locate with "X" in section below: Sketch map:
N
W E
S
1 Mile
1 Mile

6. Bore hole dia. 4 1/2 in. Completion date 2-26-76
Well depth 232 ft.

7. Cable tool Rotary Driven Dug
Hollow rod Jetted Bored Reverse rotary

8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
Lawn Oil field water Other

9. Casing: Material Steel Height: Above or below
Threaded Welded Surface P in.
RMP PVC Weight 27 lbs./ft.
Dia. 8 in. to 232 ft. depth Wall Thickness: inches or
Dia. in. to ft. depth gage No. 188

5. Type and color of material	From	To
<u>Topsoil</u>	<u>0</u>	<u>4</u>
<u>Sandstone-- Clay</u>	<u>4</u>	<u>131</u>
<u>Gravel</u> <u>Water level</u>	<u>131</u>	<u>136</u>
<u>Clay</u>	<u>136</u>	<u>139</u>
<u>Gravel</u>	<u>139</u>	<u>148</u>
<u>Sandstone</u>	<u>148</u>	<u>149</u>
<u>Gravel</u>	<u>149</u>	<u>155</u>
<u>Clay</u>	<u>155</u>	<u>161</u>
<u>Gravel</u>	<u>161</u>	<u>171</u>
<u>Sandstone</u>	<u>171</u>	<u>178</u>
<u>Gravel</u>	<u>178</u>	<u>201</u>
<u>Sandstone</u>	<u>201</u>	<u>205</u>
<u>Gravel</u>	<u>205</u>	<u>219</u>
<u>Soapstone</u>	<u>219</u>	<u>223</u>
<u>Shale</u>	<u>223</u>	<u>226</u>
<u>BROCK 219'</u>		

10. Screen: Manufacturer's name W.A. Brown
Type mill slot Dia. 16
Slot/gauze 1/4 Length 280'
Set between 1/2 ft. and 2 1/2 ft.
ft. and ft.
Gravel pack? Size range of material 1/2

11. Static water level: 131 ft. below land surface Date 1-29-76 mo./day/yr.

12. Pumping level below land surfaces:
125 ft. after 8 hrs. pumping 800 g.p.m.
210 ft. after 16 hrs. pumping 1190 g.p.m.
Estimated maximum yield 1190 g.p.m.

13. Water sample submitted: Yes No Date _____ mo./day/yr.

14. Well head completion: Pitless adapter _____ inches above grade

15. Well grouted?
With: Neat cement Bentonite Concrete
Depth: From 8' Above to 10 ft. below

16. Nearest source of possible contamination: _____ ft. _____ Direction _____ Type _____
Well disinfected upon completion? Yes No

17. Pump: Not installed
Manufacturer's name TAIT A9C
Model number 12400 HP _____ Volts _____
Length of drop pipe 220 ft. capacity 1190 g.p.m.
Type: _____ Submersible _____ Turbine _____ Jet _____ Reciprocating _____ Centrifugal _____ Other _____

18. Elevation:
Topography: Hill Slope Upland _____ Valley _____

19. Remarks:
CONCRETE WAS RUN BY Foust Supply Co.

20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Foust Supply Co. Inc 144
Business name _____ License No. _____
Address 60838 Roadland Kansas
Signed Ralph Elmer Date 6-15-76
Authorized representative

T 15 R 38 W 29 Sec 29 SW 1/4