			Form Change			ision of Water ources App. No		Well ID	
1 LOCA	Original Record Correction Change in Well Use  1 LOCATION OF WATER WELL: Fraction					tion Number		er Range Number	
County: Saline NW ½ SW ½ NE ½ SE ½ 31 T 15 S R 4 □ E ■ W									
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:									
Address: 5300 Hutchinson Street									
Address: Suite 109 MAFB City: Wichita State: KS ZIP: 67211  Smoky Hill ANG Range, 6429 W Farrely Rd., Salina, Ks. 67401									
WITH "									
	Depth(s) Groundwater Encountered: 1)					Dry Well Horizontal Datum: ■ WGS 84 □ NAD 83 □ NAD 27			
	WELL'S STATIC WATER LEVEL:33.0					ft. Source for Latitude/Longitude:			
	below land surface, measured on (mo-day-yr							)	
NW	Pump test data: Well water was						(WAAS enabled? ☐ nd Survey ☐ Topogra		
w									
sw	SWSE Well water was						4454.70		
	Estimated Yield gpm							☐ Ground Level ☐ TOC	
	S Bore Hole Diameter: 8.25 in to 43					Source:		GPS Topographic Map	
mile									
1. Domestic: 5. Public Water Supply: well ID									
	Household 6. Dewatering: how many wells?					11. Test Hole: well ID Geotechnical			
_	☐ Lawn & Garden 7. ☐ Aquifer Recharge: well ID. ☐ Livestock 8. ■ Monitoring: well ID. ☐ DP12-M					_	ed Uncased Uncased Commany bores		
_	2. Irrigation 9. Environmental Remediation: well ID					a) Closed Loop    Horizontal    Vertical			
	3. ☐ Feedlot ☐ Air Sparge ☐ Soil Vapor E							scharge Inj. of Water	
4. Industrial Recovery Injection 13. Other (specify):									
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:									
8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other									
Casing diameter									
Casing height above land surface in. Weight lbs/ft. Wall thickness or gauge No. SCD 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous Slot									
SCREEN-PERFORATED INTERVALS: From33 ft. to .43 ft., From ft. to ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 30 ft. to 43 ft., From ft. to ft., From ft. to ft., From ft.									
9 GROUT MATERIAL: □ Neat cement □ Cement grout ■ Bentonite □ Other									
Nearest source of possible contamination:									
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage									
☐ Sewer Lines     ☐ Cess Pool     ☐ Sewage Lagoon     ☐ Fuel Storage     ☐ Abandoned Water Well       ☐ Watertight Sewer Lines     ☐ Seepage Pit     ☐ Feedyard     ☐ Fertilizer Storage     ☐ Oil Well/Gas Well									
Other (Specify)									
Direction from well?									
10 FROM 0	TO 15	clay, brown		GIC LUG	FROM	TO I	ATHU. LUG (cont.) or	PLUGGING INTERVALS	
15	20	clay, brown,	JIILY						
20	38	clay, brown	lay, brown						
38	40	sand, brown	1						
40	43	clay, grey							
					Notes:				
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, or plugged under my jurisdiction and was completed on (mo-day-year) .8-18-16									
Kansas Water Well Contractor's License No. 694 This Water Well Record was completed on (mo-day-year)									
under the b	usiness nan	ne of Environ	nmental P	riority.Servicelnc.	Si	gnature 1.2	X J MI		
Mail I white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.									
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015									