## CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	Location changed to:
Section-Township-Range: 26-155-5W	26-155-4W
Fraction ( 1/4 1/4 1/4):	SW NW SW
Other changes: Initial statements:	·
Changed to:	
Comments:	
verification method: Written & legal description map, county ownership map.	ciptions, position on plat
	initials:

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

		R WELL RECORD F	orm WWC-5	KSA 82a	-1212			
1 LOCATION OF WATER	WELL: Fraction		Sect	ion Number	Township N	lumber	Range Number	
County: Saline	Lsw ½		1/4	26	T 15	S	l R 5 €W	
Distance and direction from nearest town or city street address of well if located within city?  1 1/2 miles South & 3 miles West of Smolan, KS								
1 1/2	miles South & :	miles West	of Smol	an, KS				
_	vernon Johnso	on						
RR#, St. Address, Box #		7.470					Division of Water Resources	
City, State, ZIP Code	: Smolan, KS 6	/4/9	^			n Number:		
AN "X" IN SECTION BO	TION WITH 4 DEPTH OF C							
. N	Depth(s) Ground							
<b>†</b>	. !!						4299.2	
NW	NF + + 1 1					•	mping gpm	
<u> </u>		Est. Yield 8-1.0. gpm: Well water was30 ft. after3/4 hours pumping 8-1.0 gpm  Bore Hole Diameter8in. to53ft., andin. toft.						
* w   1			Public water		8 Air conditionin		Injection well	
7 1 1	1 Domestic					•	Other (Specify below)	
SW	SE 2 Irrigation	4 Industrial 7	Lawn and or	arden only	10 Monitorina we		Stock	
	• • •		-	•	-		, mo/day/yr sample was sub-	
<u> </u>	mitted				ter Well Disinfect	-		
5 TYPE OF BLANK CASH		5 Wrought iron	8 Concre				d . X Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (	specify below			ed	
2 PVC	4 ABS	7 Fiberglass					aded	
	5in. to40							
	surface1.2	.in., weight 2 .	3.7	Ibs./	ft. Wall thickness	or gauge N	o <b>214</b>	
TYPE OF SCREEN OR PE	ERFORATION MATERIAL:		7 PV		10 As	bestos-ceme	ent	
1 Steel	3 Stainless steel	5 Fiberglass		P (SR)				
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	8		one used (op	·	
SCREEN OR PERFORATI			wrapped		8 Saw cut		11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire w	• •		9 Drilled holes			
2 Louvered shutter	4 Key punched	7 Torch (		4				
SCREEN-PERFORATED II							oft.	
GRAVEL PACK I							ιο	
GIAVEE FAOR I			J ()					
6 GROUT MATERIAL:	1 Neat cement		3 Bentor					
Grout Intervals: From	5ft. to 25							
	of possible contamination:						bandoned water well	
_	4 Lateral lines		-		storage	15 C	il well/Gas well	
2 Sewer lines	5 Cess pool	8 Sewage lagor	on	12 Fertil	izer storage	16 C	Other (specify below)	
3 Watertight sewer lii	nes 6 Seepage pit	9 Feedyard		13 Insec	ticide storage			
Direction from well?			1	How ma		N HAARIA	NTES	
FROM TO	LITHOLOGIC	LOG	FROM	то	F	PLUGGING I	NIERVALS	
	Top Soil		<b> </b>					
1	Tan Clay		-					
	Gray Clay							
28 31	Tan Clay							
	Sand-Fine							
·	Course Creek G:							
30 33	Green Shale							
	4- 18-19-19-19-19-19-19-19-19-19-19-19-19-19-							
	,							
7 CONTRACTOR'S OR L	ANDOWNER'S CERTIFICAT	TION: This water well wa	s (1) construc	cted, (2) reco	onstructed, or (3)	plugged und	der my jurisdiction and was	
	r) 4-29-							
	cense No 1.38							
under the business name of	of Peterson Irri	gation, Inc/		by (signa	iture) Mi	u W	etoso-	
INSTRUCTIONS: Use typewri	iter or ball point pen. <u>PLEASE PRESS</u> Bureau of Water, Topeka, Kansas 666	FIRMLY and PRINT clearly. Plea	se fill in blanks, u	underline or circl	e the correct answers	Send top three	copies to Kansas Department	
I of Hoolth and Endagence					WALKER AND TOTAL ONC			