


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WESKAN

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

BBB

1. Location of well: County <u>Wallace</u> Fraction <u>NW<sup>1</sup>/<sub>4</sub> NW<sup>1</sup>/<sub>4</sub> NW<sup>1</sup>/<sub>4</sub></u> Section number <u>8</u> Township number <u>T 25 S R 41 E/W</u> Range number	
2. Distance and direction from nearest town or city: <u>SHARON SPRINGS</u> Street address of well location if in city: <u>8-5 9-W.</u>	
3. Owner of well: <u>VIVIAN COX</u> R.R. or street: City, state, zip code: <u>ARRIBA COLORADO 80804</u>	
4. Locate with "X" in section below: Sketch map: N W E S 1 Mile 	
6. Bore hole dia. <u>2 1/2</u> in. Completion date <u>12-20-76</u> Well depth <u>176</u> ft.	
7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
8. Use: Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
9. Casing: Material <u>Steel</u> Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface <u>12</u> in. RMP <u>PVC</u> Weight <u>36</u> lbs./ft. Dia. <u>1 1/2</u> in. to <u>1 1/2</u> ft. depth Wall Thickness: inches or Dia. <u>1 1/2</u> in. to <u>1 1/2</u> ft. depth gage No. <u>219</u>	
10. Screen: Manufacturer's name <u>W.A. Brown</u> Type <u>Louven</u> Dia. <u>1 1/2</u> Slot/gauze <u>1/8" x 7/8"</u> Length <u>50</u> Set between <u>146</u> ft. and <u>196</u> ft. ft. and <u>196</u> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material <u>1/4" x 3/8"</u>	
11. Static water level: <u>135</u> ft. below land surface Date <u>11-5-76</u> mo./day/yr.	
12. Pumping level below land surfaces: <u>185</u> ft. after <u>5</u> hrs. pumping <u>950</u> g.p.m. <u>    </u> ft. after <u>    </u> hrs. pumping <u>    </u> g.p.m. Estimated maximum yield <u>1000</u> g.p.m.	
13. Water sample submitted: <u>    </u> mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date <u>    </u>	
14. Well head completion: <input type="checkbox"/> Pitless adapter <u>    </u> inches above grade	
15. Well grouted? <input checked="" type="checkbox"/> <u>YES</u> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From <u>0</u> ft. to <u>10</u> ft.	
16. Nearest source of possible contamination: ft. <u>    </u> Direction <u>    </u> Type <u>None</u> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
17. Pump: <input type="checkbox"/> Not installed Manufacturer's name <u>Weston and Patton</u> Model number <u>8M</u> HP <u>80</u> Volts <u>    </u> Length of drop pipe <u>180</u> ft. capacity <u>900</u> g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
(Use a second sheet if needed)	
18. Elevation: Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks: <u>3763 (TOPO)</u>
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>L.H. Dunning Co Inc 166</u> Business name <u>    </u> License No. <u>    </u> Address <u>    </u> Signed <u>B. C. [Signature]</u> Date <u>12-22-76</u> Authorized representative	

T 25 R 41 E  
S 8  
N 1/4 W 1/4 N 1/4