WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

		BBA						(Water well Contractors) Topeka, Kansas 66620	
1. Location of well:	County	Fraction	;		Section	number	Township number	Range number	
	Wallace						т 15	S R 41	(E)w
2. Distance and direc	ction from nearest town or city: 8 I	ni. S., 5 Sharon Spi			er of well	: De	ewigh ; Blaesi		
Street address of well	location if in city: Kar		r mgs,			ode: St	naron Springs	s. Ks. 67758	
4. Locate with "X" in section below: N							4 Bara hala dia 28	in. Completion date	
	1						7 Cable tool I Hollow rod	Rotary Driven Dug letted BoredX Reve	
\\\	NE						8. Use: Domestic		
							X Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material Steel Height: Above or below		
sw se									
<u> </u>							Threaded Welded		in. _lbs./ft.
1 Mi		,	,		,		Dia 16 in. to 250	t. depth Wall Thickness: inc	ches or
5. Type and color of material					From	То	Diain. to f	t. depth gage No. <u>215</u> prer's name	
Top soil	& clay				0	15	W. A. Br	own	
Clay & little lime					15	4	Slavenze Perf.	2" Length 40 f	t.
					155	Set between 250	ft. and ft. and	ft.	
Name of the second seco					1.55	⁹ 1.83-	Gravel pack? <u>Ves</u> S		2/8 /d=:/==
Clay (white & gumy)					183	190	160 ft. below to	and surface Date <u>4–28</u>	/day/yr. ·76
Sand & white clay streaked					190	195	12. Pumping level belo	w land surfaces:hrs.pumping 1500)
Sand		en e			195	224	ft. after	hrs. pumping	. g.p.m.
Cemented Sand					224	225	Estimated maximum yie 13. Water sample subm		_g.p.m. /day/yr.
Sand	popular se in mangang tilan se mangan menganan menganan menganan se	الموالية والمرازع	1.5	g a veggjallag yar er gri vi da ya bad	225	233	Yes X N		
						. •	Pitless adapter 12 Inches above grade		
Clay					233	244	15. Well grouted? <u>YES</u> With: Neat cement X Bentonite Concrete		
Sand					244	25 8	Depth: FromO		-
Clay & Lime streaked					258	269	16. Nearest source of p	possible contamination: Type NON	e
Sand					269	273	Well disinfected upon	completion?Yes _	
Clay (ye kk ow)					273	2 85	17. Pump: Manufacturer's name _	X Not installed	
Shale					285	290	Model number Length of drop pipe	HP Vol	
	BROCK	772.					Type: Submersible	, ,	
							Jet	Turbine Recipro	
18. Elevation:	(Use a second si	heet if needed)					Centrifugal	Other	*
Level						This well was drilled u	nder my jurisdiction and this	report	
Тородгарну:								knowledge and belief. PUMP & SUPPLY	123
— Hill — Slope							Business name Box		ense No.
Upland							Signed 70	ve Saits	6-30 2
Valley							Authoriz	ed representative	}