


1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 County: ELLSWORTH SE 1/4 SE 1/4 NE 1/4 4 T 15 S R 6 E/W

Distance and direction from nearest town or city street address of well if located within city?

1/2 MILE WEST OF K-40 & K-141 1 1/2 MILES NORTH

2 WATER WELL OWNER: JACK LILL Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: P. O. BOX 123 Application Number:
 City, State, ZIP Code: BROOKVILLE, KS 67425

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 152 ft. ELEVATION: 1580

 Depth(s) Groundwater Encountered 101 ft. 2. 102 ft. 3. 12-31-91 ft.
 WELL'S STATIC WATER LEVEL 102 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 1 1/2 ft. after 12 hours pumping 12 gpm
 Est. Yield 20 gpm: Well water was 152 ft. after 12 hours pumping 12 gpm
 Bore Hole Diameter 9 in. to 152 ft. and 152 in. to 152 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 112 ft., Dia 112 in. to 160 ft., Dia 160 in. to 160 ft.
 Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 112 ft. to 152 ft., From 152 ft. to 152 ft.
 From 68 ft. to 152 ft., From 152 ft. to 152 ft.
 GRAVEL PACK INTERVALS: From 68 ft. to 152 ft., From 152 ft. to 152 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 5 ft. to 25 ft., From 25 ft. to 152 ft., From 152 ft. to 152 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NORTH How many feet? OVER 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOP SOIL			
1	11	CLAY BROWN			
11	18	CLAY TAN W/RED LAYERS			
18	27	CLAY RED			
27	43	SANDSTONE TAN			
43	53	CLAY RED W/GRAY LAYERS			
53	74	CLAY GRAY			
74	78	CLAY DARK GRAY			
78	100	CLAY LIGHT GRAY			
100	101	SANDSTONE CEMENTED			
101	152	SANDSTONE TAN W/CLAY LAYERS GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-29-91 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 12-31-91
 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

9122819018