			WATER	WELL RECORD	Form WWC	-5 KSA 82a	-1212	
1 LOCATI	ON OF WAT		Fraction		1	ection Number	Township Number	Range Number
County:	Ellswor		NE 1/4		VE 1/4	36	т 15 s	R 8 X2XW
Distance a			· · · · · · · · · · · · · · · · · · ·	dress of well if locat	ed within city	?		
			Kanopolis, I					
2 WATE	R WELL OW	NER: City o	f Kanopo N s					
RR#, St.	Address, Box	# : 119 N.	Kansas				Board of Agricultu	re, Division of Water Resources
City, State	, ZIP Code	: Kanopo	lis, KS 674	54			Application Numb	er:
LOCAT	E WELL'S LO	CATION WITH	4 DEPTH OF CO	MPLETED WELL		30 . ft. ELEVA	TION:	
- AN "X"	IN SECTION	BOX:	Depth(s) Groundw	vater Encountered	1		2	ft. 3
ī	ı	ıX	WELL'S STATIC	WATER LEVEL	<i>.</i> ft.	below land sur	face measured on mo/da	y/yr
1	NW	1	Pump	test data: Well was	ter was	ft. a	fter hours	s pumping gpm
	NW	NE	Est. Yield	1 gpm: Well wat	ter was	ft. a	ifter hours	s pumping gpm
<u>.</u> l	i		Bore Hole Diamet	er8.in. to)	3 0 ft.,	and	in. to
* w	1	1	WELL WATER TO	D BE USED AS:		ter supply		11 Injection well
7	1		1 Domestic	3 Feedlot	6 Oil field v	ater supply	9 Dewatering	12 Other (Specify below)
	SW	SE	2 Irrigation	4 Industrial	7 Lawn and	garden only _	10 Monitoring wellMM	/15
1 1	i		Was a chemical/ba	acteriological sample	submitted to	Department? Y	es; If	yes, mo/day/yr sample was sub-
1 -	S		mitted	-		Wa	ter Well Disinfected? Yes	s No X
5 TYPE	OF BLANK C	ASING USED:		5 Wrought iron	8 Con	crete tile	CASING JOINTS: 0	Glued Clamped
 1 St	eel	3 RMP (SF	R)	6 Asbestos-Cement	9 Othe	r (specify below	v)	Velded
2 P\	/C	4 ABS		7 Fiberglass				Threaded X
Blank casi	ing diameter	2	.in. to	. 20 ft., Dia				in. to ft.
Casing he	ight above la	nd surface	 5 i	in., weight		.20 lbs.	ft. Wall thickness or gaug	ge No Sch 40
TYPE OF	SCREEN OF	R PERFORATIO	N MATERIAL:	_	7 F	VC	10 Asbestos-c	cement
1 St	eel	3 Stainless	s steel	5 Fiberglass	8 F	MP (SR)	11 Other (spe	cify)
2 Br	ass	4 Galvaniz	ed steel	6 Concrete tile	9 A	BS	12 None used	(open hole)
SCREEN	OR PERFOR	RATION OPENIN	GS ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)
1 Co	ontinuous slo	t 3 M	ill slot	6 Wire	wrapped		9 Drilled holes	
2 Lo	ouvered shutt	er 4 Ke	ey punched	7 Toro	h cut		10 Other (specify)	
SCREEN-	PERFORATE	D INTERVALS:	From	2 0 ft. to .		.30ft., Fro	m	ft. toft.
			From	ft. to .		ft., Fro	m <i></i>	$ft.\ to.\dots\dots.ft.$
(GRAVEL PAG	CK INTERVALS:	From	16 ft. to .		30 ft., Fro	m	ft. toft.
			From	ft. to		ft., Fro	m	ft. to ft.
6 GROU	T MATERIAL	: 1 Neat o	cement 2	2 Cement grout			Other Concrete	:
Grout Inte	rvals: From	n 2 .	. ft. to	16 ft., From	ft.	to	. 2 . ft., From	ft. toft.
What is th	ne nearest so	urce of possible	contamination:			10 Lives	tock pens 1	4 Abandoned water well
1 Septic tank 4 Lateral I		al lines	7 Pit privy		11 Fuel	storage 1	5 Oil well/Gas well	
2 Sewer lines 5 Cess			8 Sewage lagoon			izer storage 1	6 Other (specify below)	
3 W	atertight sew	er lines 6 Seep	age pit	9 Feedyard		13 Insec	cticide storage	Salt Mine
Direction	from well?					How ma	ny feet?	800'
FROM	ТО		LITHOLOGIC L	.OG	FROM	то	PLUGGI	NG INTERVALS
0	4	Loamy cla	y, dk. brow	n to brn yel	low			
4	30	Sand, bro	wnish yello	w, coarse gr	eih			
							—	
		A SECTION OF SECTION						
		· · · · · · · · · · · · · · · · · · ·						
				•		1		
							LV IV IV IV	
7 CONTI	RACTOR'S	R LANDOWNER	R'S CERTIFICATIO	ON: This water well	was (1) const	ructed. (2) reco	onstructed, or (3) plugged	under my jurisdiction and was
-		year) 5/28/						y knowledge and belief. Kansas
							on (mo/day/yr) 15/.1/	
under me	business nar							
		me of J&R	Orilling Se	rvices, Inc.		by (signa	iture) Kay Com	three copies to Kansas Department