

1 LOCATION OF WATER WELL: County: ELLISWORTH Fraction: SE 1/4 NE 1/4 SW 1/4 Section Number: 200 Township Number: T 15 S Range Number: R 08 EW

Distance and direction from nearest town or city street address of well if located within city? CENTRAL KANSAS MILL & ELEVATOR CO. SOUTH COLORADO STREET ELLISWORTH, KS.

2 WATER WELL OWNER: JOHNSON ELEVATOR INC. RR#, St. Address, Box #: P.O. BOX 57 City, State, ZIP Code: MENTOR, KS. 67465 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of section box with X in SW quadrant] 4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 1535. Depth(s) Groundwater Encountered: 1. 27 1/2 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 27 1/2 ft. below land surface measured on mo/day/yr: 8-11-89. Pump test data: Well water was NA ft. after hours pumping gpm. Est. Yield: NA gpm: Well water was ft. after hours pumping gpm. Bore Hole Diameter: 6 in. to 35 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well. Was a chemical/bacteriological sample submitted? Yes No X; If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded X. Blank casing diameter: 2 in. to 22 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 24 in., weight lbs./ft. Wall thickness or gauge No. SDR: -21. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot .010 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 32 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other HOLE PLUG. Grout Intervals: From 0 ft. to 16 ft., From 16 ft. to 20 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below). Direction from well? EAST How many feet? 45

LITHOLOGIC LOG table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-3 TOP SOIL, 3-18 DARK GRAY SILTY CLAY, 18-23 SANDY LOAM, 23-28 SAND, 28-32 MED. SAND & GRAVEL.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-11-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388. This Water Well Record was completed on (mo/day/yr) 8-11-89 under the business name of PESTINGER PUMP SERVICE by (signature) Paul Pestinger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.