

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Ellsworth		NW ¼ NW ¼ NE ¼		28		T 15 S		R 8 EW			
Distance and direction from nearest town or city street address of well if located within city?											
1 mile south and 1/8 mi E of Intersection of 140 & 156 Hwys MW#3											
2 WATER WELL OWNER: St. Francis Academy, Inc.											
RR#, St. Address, Box #: P.O.Box 127 Board of Agriculture, Division of Water Resources											
City, State, ZIP Code: Ellsworth, Ks. 67439 Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 29.5 ft. ELEVATION:								
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.								
			WELL'S STATIC WATER LEVEL: 29.50 ft. below land surface measured on mo/day/yr 7-29-91								
			Pump test data: Well water was ft. after hours pumping gpm								
			Est. Yield gpm: Well water was ft. after hours pumping gpm								
			Bore Hole Diameter: 7 5/8 in. to 29.5 ft., and in. to ft.								
WELL WATER TO BE USED AS:											
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes No <u>X</u>											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u>											
Blank casing diameter 2 in. to 14.5 ft., Dia in. to ft., Dia in. to ft.											
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From 14.5 ft. to 29.5 ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From 11 ft. to 29.5 ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement <u>2 Cement grout</u> <u>3 Bentonite</u> 4 Other											
Grout Intervals: From 0 ft. to 8.5 (cement) ft. to 11 (bent) ft., From ft. to ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon <u>11 Fuel storage</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage											
Direction from well? North How many feet? 100											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		2		Clay, black							
2		15.5		Clay, brown, sandy, silty							
15.5		19		Sand, yellow, fine to coarse							
19		27		Sand, yellow, medium to coarse							
27		29		Clay, reddish yellow, sandy, silty							
29		29.5		Shale, grey, sandy							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-9-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7-20-91 under the business name of GeoCore Services, Inc. by (signature) Dale G. Bell											