1 10047	1011 05 141		TER WELL RE	CORD	Form WV	VC-5	KSA 82a-								
1 LOCATION OF WATER WELL: Fraction County: ELLSWORTH NE 1/4					CN CD			tion Number	1	Township Number			Range Number		
				SW		SE ¼		20	<u>  T</u>	15	S	l R	8	E/W	
Distance a	nd direction	from nearest to	wn or city street	address of	f well if lo	cated wi	thin city?								
	DOUGLA	AS & MAIN	, 104 N.	. DOUG	LAS										
2 WATER	R WELL OW	NER: MART	IN OIL	COMPAN	ΙY										
RR#, St. A.	ddress, Box		N. DOUGI		20					ard of Agri			of Water F	Resources	
		CATION WITH	WORTH, I	(S 6/4	39	31	. 65	# ELEVA							
	NELL'S LO														
AN A 11	N SECTION N	BOX.	Depth(s) Grou WELL'S STAT	Indwater E	ncountere	°27	26 ft held	II	. 2	d on mo/c	π. Hav/vr	32-17	-05	π.	
	1		Pu	imp test da	ata: Wel	l water v	vas	ft.	after	u 011 1110/0	hours	pumpina		apm	
İ	NBA/	\_	Est. Yield												
-	-NW	NE	WELL WATER				blic water s		8 Air cond	-		Injection			
	; }		1 Domesti		edlot			supply	9 Dewate			Other (Sp			
w	1	E	2 Irrigation	1 4 IN	dustrial	7 00	mestic (lav	vn & garden)	N Avionitor	ing well	•••••	••••••	••••••		
	1	1													
-	-SW -	SE       X	Was a chemic	al/bacterio	logical sa	mple su	bmitted to I					mo/day/y			
	·	^	mitted					W	ater Well D	isinfected	? Yes		N	oχχ	
L	S	<u> </u>													
5 TYPE	OF BLANK	CASING USED:		5 Wrou	ght iron		8 Concre	ete tile	CAS	ING JOIN	ITS: Glu	ed	. Clampe	ed	
1 Steel 3 RMP (SR)					6 Asbestos-Cement			(specify below					ded		
XX 2 PVC	;	4 ABS		7 Fiber	-										
		2.!!													
		and surface2		in., v	veight				lbs./ft. Wal	l thicknes	s or gua	age No. <b>S</b> .	CH4.0	1	
TYPE OF SCREEN OR PERFORATION MATERIAL:							XX PV			10 Asbe					
1 Stee		3 Stainless			5 Fiberglass 6 Concrete tile			1P (SR)							
2 Bras		4 Galvaniz		6 Conc	rete tile		9 AB	3		12 None	usea (	open hole	)		
SCREEN (	OR PERFO	RATION OPENIN					l wrapped		8 Saw o			11 No	ne (open	hole)	
	tinuous slot	XXV	lill slot . 01 (	0		Wire wr Torch co			9 Drilled					ft.	
	vered shutte		ey punched												
SCREEN-	PERFORAT	ED INTERVALS:						ft., From							
(	SRAVEL PA	CK INTERVALS						ft., From ft., From							
`	JII) (V LL 1 7	OKINTENVALO						ft., From							
	10/20	SAND													
	IT MATERIA			2 Cer	_			onite							
Grout Inter	vals: Fro	m1.48	ft. toQ.	ft.	, From		ft. t	o	ft., Fro	m		ft. to .		ft.	
What is the	e nearest so	ource of possible	contamination:					10 Livest	tock pens		14	Abandon	ed water	well	
1 Septic tank 4 Lateral lines					7 Pit privy			11 Fuel storage			15 Oil well/Gas well				
2 Sewer lines 5 Cess pool					8 Sewage lage			goon 12 Fertilizer storage			16 Other (specify below)				
XX3 Wat	ertight sew	er lines 6 Seep		9 Feedyard			13 Insecticide storage								
Direction fr	om well?	WEST						How man	ny feet?	15 <b>'</b>					
FROM	то		LITHOLOGI	C LOG			FROM	ТО		PLUC	GING I	NTERVA	_S		
0	5	TOP SOI	L CLAY	BASE											
5	10		OWN CLA												
10	15		ROWN SIL		Y										
15	20		OWN CLA		•										
20	25	TAN SAN		•											
25	30		ID - WAT	EB						4	_				
30	35	SAND	D - WAII						MM	<del>/ 1/</del>	7				
	35	SAND							- //I M	<u></u>	<del>/</del>				
														-	
7															
		OR LANDOWNE													
		year)21.7											and beli	er. Kansas	
		s Licence No							-	ay/yr)			//		
		ne of PRATT							signature)	M	verj	24	4		
		ewriter or ball point pe of Water, Geology Se													
		each constructed well.		_ J July Julie .	, ropona,				Jona Oile	7	011		3/10 IOI y		