

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Ellsworth	NW ¼ NE ¼ NW ¼	21	T 15 S	R 8 EW

Distance and direction from nearest town or city street address of well if located within city?

515 Novak, Ellsworth

2 WATER WELL OWNER:	Bob Steele	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	515 Novak	Application Number:
City, State, ZIP Code :	Ellsworth, KS	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 131 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 75 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 10 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter. 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. X Clamped.
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 91 ft., Dia.			11 Other (specify)
Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No.			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	
1 Steel	3 Stainless steel	9 ABS	
2 Brass	4 Galvanized steel		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 91 ft. to 131 ft., From			
GRAVEL PACK INTERVALS: From 20 ft. to 131 ft., From			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well? South	How many feet? 40			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Clay			
3	35	Sand (f-m)			
35	45	Sand (m-vc)			
45	65	Shale - gray			
65	68	Shale with sandstone lenses			
68	73	Shale - gray			
73	88	Shale - red and gray			
88	94	Sandstone			
94	98	Shale			
98	114	Sandstone			
114	118	Shale			
118	133	Sandstone			
133	135	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/8/2007 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 527. This Water Well Record was completed on (mo/day/yr) 8/27/2007 under the business name of GeoCore Inc. by (signature) [Signature]
--