

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: Ellsworth, Fraction: 1/4 NW 1/4 NE 1/4 SE 1/4, Section Number: 24, Township No.: T 15 S, Range Number: R 8, Global Positioning System (GPS) information: Latitude: 38.73208, Longitude: 098.15408, Elevation: , Datum: WGS 84, NAD 83, NAD 27, Collection Method: GPS unit, Digital Map/Photo, Topographic Map, Land Survey, Est. Accuracy: <3 m, 3-5 m, 5-15 m, >15 m

2 WATER WELL OWNER: Michael Caleb Svaty, RR#, Street Address, Box #: 1050 Hwy 111, City, State, ZIP Code: Kanopolis, KS 67454, 3 LOCATE WELL WITH AN "X" IN SECTION BOX: N, E, S, W, 4 DEPTH OF COMPLETED WELL 176 ft., Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft., WELL'S STATIC WATER LEVEL 95 ft. below land surface measured on mo/day/yr. 9-15-15, Pump test data: Well water was ft. after hours pumping gpm, EST. YIELD N/A gpm. Well water was ft. after hours pumping gpm, Bore Hole Diameter 10 in. to 176 ft., and in. to ft., WELL WATER TO BE USED AS: Domestic, Feedlot, Oil field water supply, Geothermal, Injection well, Irrigation, Industrial, Domestic-lawn & garden, Dewatering, Other (Specify below), Was a chemical/bacteriological sample submitted to Department? Yes, No, If yes, mo/day/yr sample was submitted, Water well disinfected? Yes, No

5 TYPE OF CASING USED: Steel, PVC, Other, CASING JOINTS: Glued, Clamped, Welded, Threaded, Casing diameter 5 in. to 176 ft., Diameter in. to ft., Diameter in. to ft., Casing height above land surface 18 in., Weight SDR 21 lbs./ft., Wall thickness or gauge No., TYPE OF SCREEN OR PERFORATION MATERIAL: Steel, Stainless Steel, PVC, Brass, Galvanized Steel, None used (open hole), Other (Specify), SCREEN OR PERFORATION OPENINGS ARE: Continuous slot, Mill slot, Gauze wrapped, Torch cut, Drilled holes, None (open hole), Louvered shutter, Key punched, Wire wrapped, Saw cut, Other (specify), SCREEN-PERFORATED INTERVALS: From 176 ft. to 156 ft., From ft. to ft., From ft. to ft., GRAVEL PACK INTERVALS: From 176 ft. to 20 ft., From ft. to ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement, Cement grout, Bentonite, Other, Grout Intervals: From ft. to ft., From 20 ft. to 0 ft., From ft. to ft., What is the nearest source of possible contamination: Septic tank, Lateral lines, Pit privy, Livestock pens, Insecticide storage, Other (specify below), Sewer lines, Cesspool, Sewage lagoon, Fuel storage, Abandoned water well, Watertight sewer lines, Seepage pit, Feedyard, Fertilizer storage, Oil well/gas well, House, Direction from well West, Distance from well 1000ft

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-4 Top soil, 4-13 Sandy, gray clay, 13-34 Sand & gravel, 34-59 Fire clay, 59-89 Gray shale, 89-94 Sandstone & shale, 94-155 Gray shale & iron pyrite, 155-176 Sandstone, shale, & iron pyrite

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 9-15-15 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 9-30-15 under the business name of Rosenkrantz-Bemis Ent Inc by (signature) Tom White

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html