

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Saline		N W 1/4 N W 1/4 N W 1/4	11	T 16 S	R 1 E (W)
Distance and direction from nearest town or city street address of well if located within city?					
1 mile east and 1 1/2 south of Gypsum, Ks.					
2 WATER WELL OWNER: Dwight Swisher		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : 904 Tulane		Application Number:			
City, State, ZIP Code : Salina, Ks. 67401					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 47 ft. ELEVATION:			
1 Mile		Depth(s) Groundwater Encountered 1. 38 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 8-7-82			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 25+ gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 47 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
Was a chemical/bacteriological sample submitted to Department? Yes No * ; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes * No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued * Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded					
2 PVC 4 ABS 7 Fiberglass Threaded					
Blank casing diameter 5 in. to 47 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 36 in., weight 160 SDR 26 lbs./ft. Wall thickness or gauge No. 0.258					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 35 ft. to 47 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 13 ft. to 47 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 13 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? South		How many feet? 1/4 mile			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	Brown Sandy Clay			
15	26	Light Color Clay			
26	28	Light Gray Clay			
28	32	Blue Clay Soft			
32	36	Soft Gray Clay & Shale			
36	43	Light Color Shale			
43	46	Blue Clay			
46	47	Gypsum & Hard Dark Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/7/82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 397 This Water Well Record was completed on (mo/day/yr) 8-9-82 under the business name of CENTRAL KANSAS DRILLING by (signature) Harold D. Martin					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					