11 None (open hole)

16 Other (specify below)

Osage

1 LOCATION OF WATER WELL:

2 WATER WELL OWNER: Chevron Environmental Management Company RR#, St. Address, Box # : 2300 Windy Ridge Parkway, Suite 575

Fraction

SW 1/4

Atlanta, Georgia 30339-5665

Board of Agriculture, Division of Water Resources

Application Number:

Township Number

16

Х 룵 W Ε

S

2 Louvered shutter

TO

FROM

LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 14.0 ft. ELEVATION: **12.0** ft. 2 ft. 3 ft. Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 6.20 ft. below land surface measured on mo/day/yr 10/12/06 Pump test data: Well water was ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8.5 in. to 14.0 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply
1 Domestic 3 Feed lot 6 Oil field water supply
9 Dewatering 12 Other (Specify below)

Section Number

11 Injection well
12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden (domestic) (0) Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X

TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile	CASING JOIN	NTS: Glued	Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	t 9 Other (specify	below)	Welded	
②PVC 4 ABS	7 Fiberglass			Threaded	X
llank casing diameter 2.375 in. to	o 4.0 ft., Dia	in. to	ft., Dia	in. to	ft
asing height above land surface Flush	Mount in., weight	lbs	s./ft. Wall thickness or	gauge No. Scl	nedule 40

TYPE OF SCREEN OR PERFORATION MATERIAL: (7) PVC 10 Asbestos-cement 11 Other (specify) 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 9 ABS 6 Concrete tile 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut (3) Mill slot 1 Continuous slot 6 Wire wrapped 9 Drilled holes

Cement grout

10 Other (specify) Key punched 7 Torch cut ft. to 4.0 ft. From ft. to ft. SCREEN-PERFORATED INTERVALS: From

ft. to ft. From ft. to ft.

14.0 ft. to 3.0 ft. From ft. to ft. GRAVEL PACK INTERVALS: From ft. From From 6 GROUT MATERIAL: 3 Bentonite

Grout Intervals From 0.0 ft. to 1.0 ft. From 1.0 ft. to 3.0 ft. From ft. to ft. 10 Livestock pens
11 Fuel storage (former) What is the nearest source of possible contamination: 14 Abandoned water well 1 Septic tank 7 Pit privy 4 Lateral lines 15 Oil well/ Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well?

1 Neat cement

12 Fertilizer storage 13 Insecticide storage How many feet?

LITHOLOGIC LOG 0.0 1.0 Asphalt/Concrete 1.0 12.0 Brown silty clay, firm-very firm, moist Brown-orange brown silty clay, gravely, trace sand, very firm, moist 12.0 12.5 12.5 14.0 Shale and limestone, wet

Flush-mount well completion waiver approved by Don Taylor, KDHE-BOW

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 10/10/06 and this record is true to the best of my knowledge and belief/ Kansas

This Water Well Record was completed on (moday/yr) 10/16/06 Water Well Contractor's License No. Quad State Services, Inc. under the business name of by (signature)

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Byreau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.