


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Rush</u>	<u>NC 1/4 N 1/2 NE 1/4</u>	<u>36</u>	<u>T 16 S</u>	<u>R 16 E/W</u>

Distance and direction from nearest town or city street address of well if located within city?
6 North, 1/2 East of Otis, South side of road

2 WATER WELL OWNER: <u>Steve Schneider</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>897 NW 120 Ave</u>	Application Number: <u>RHW2774</u>
City, State, ZIP Code : <u>Olmitz, Ks. 67564</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>300</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>120</u> ft. below land surface measured on mo/day/yr <u>5-4-04</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>N/A</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well <u>Stock</u>
	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>HTH</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter <u>5</u> in. to <u>240</u> ft., Dia	<u>36</u> in. weight	<u>SDR-21</u> lbs./ft. Wall thickness or guage No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
			9 ABS
			10 Asbestos-Cement
			11 Other (Specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	10 Other (specify)
			11 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>300</u> ft. to <u>240</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From <u>300</u> ft. to <u>20</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>hole plug</u>
Grout Intervals: From <u>20</u> ft. to <u>0</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>None</u>
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil	255	261	Clay
2	15	Clay	261	300	Sand rock
15	85	Shale			
85	100	Clay			
100	130	Shale			
130	145	Clay & shale mix			
145	159	Clay			
159	190	Sand rock mix clay			
190	198	Clay			
198	200	Sand rock			
200	205	Clay, sandrock mix fire clay			
205	230	Clay			
230	250	Sandrock			
250	255	Fire Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-4-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 134. This Water Well Record was completed on (mo/day/yr) 5-21-04 under the business name of Rosencrantz- Bemis by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.