

1 LOCATION OF WATER WELL: County: SALINE		Fraction NW ¼ SW ¼ SW ¼	Section Number 7	Township Number T 16 S	Range Number R 2 EW
Distance and direction from nearest town or city street address of well if located within city? 9173 S. OHIO					
2 WATER WELL OWNER: RYAN ISAACSON RR#, St. Address, Box # : 9173 S. OHIO City, State, ZIP Code : ASSARIA, KS. 67416		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N --- NW --- NE --- W X E --- SW --- SE --- S		4 DEPTH OF COMPLETED WELL 63 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 21 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 11-19-98 Pump test data: Well water was 26 ft. after 3 hours pumping 30 gpm Est. Yield 75+ gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 63 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes..... No... X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 5 in. to 53 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 24 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued .. X .. Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded..... SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot .035 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 53 ft. to 63 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 47 ft. to 63 ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 26 ft., From 44 ft. to 47 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage OPEN AREA NONE APPARENT		Direction from well? How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL			
2	18	CLAY TAN SILTY			
18	63	SAND FINE TO MED TAN TO LIGHT BROWN			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-19-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 11-19-98 under the business name of PESTINGER PUMP SERVICE by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

SEC

1/4