


1 LOCATION OF WATER WELL: County: Ness Fraction: NE 1/4 NE 1/4 NE 1/4 Section Number: 2 Township Number: T 16 S Range Number: R 21 E (W)

Distance and direction from nearest town or city street address of well if located within city?
9 North 3 West 1/8 South of McCrackan Ks

2 WATER WELL OWNER: James Sarkis DR.
 RR#, St. Address, Box #: 721 GUERMSEY
 City, State, ZIP Code: Salina KS 67401
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 19 ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr 7/13/90
 Pump test data: Well water was 19 ft. after 1/2 hours pumping 8 gpm
 Est. Yield 10 gpm: Well water was . ft. after . hours pumping gpm
 Bore Hole Diameter: 10 in. to . ft., and . in. to . ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes. . No. If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 5 in. to . ft., Dia. . in. to . ft., Dia. . in. to . ft.
 Casing height above land surface: 30 in., weight . lbs./ft. Wall thickness or gauge No. SDR 24
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 15 ft. to 35 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 35 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 15 ft., From . ft. to . ft., From . ft. to . ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southeast How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	top soil			
10	15	brown clay			
15	24	fine to med Red & grey sand			
24	29	brown clay mixed with layers of fine grey sand			
29	35	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 7/16/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 276 This Water Well Record was completed on (mo/day/yr) 7/16/90 under the business name of Luza Water Well Drilling by (signature) John

OFFICE USE ONLY
T
R
EW
SEC.