


1 LOCATION OF WATER WELL: County: NESS Fraction: SC 1/4 NE 1/4 NW 1/4 Section Number: 29 Township Number: T 16 S Range Number: R 21 EW

Distance and direction from nearest town or city street address of well if located within city?  
3.5 miles EAST of Brownell Ks. 67521

2 WATER WELL OWNER: John H Irvin  
 RR#, St. Address, Box #: RR#1 Box 9 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: McCracken Ks 67556 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  


4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 16 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 17 ft. below land surface measured on mo/day/yr 3-18-92  
 Pump test data: Well water was 10 ft. after 1 hours pumping 16 gpm  
 Est. Yield 16 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 10 in. to ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic  3 Feedlot  6 Oil field water supply  9 Dewatering  12 Other (Specify below)  
 2 Irrigation  4 Industrial  7 Lawn and garden only  10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes  No  If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes  No

5 TYPE OF BLANK CASING USED:  
 1 Steel  3 RMP (SR)  5 Wrought iron  8 Concrete tile  CASING JOINTS:  Glued  Clamped  
 2 PVC  4 ABS  7 Fiberglass  Welded   
 Blank casing diameter: 6 in. to ft., Dia. in. to ft., Dia. in. to ft.  
 Casing height above land surface: 24 in., weight lbs./ft. Wall thickness or gauge No. SDR26  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel  3 Stainless steel  5 Fiberglass  7 PVC  10 Asbestos-cement   
 2 Brass  4 Galvanized steel  6 Concrete tile  8 RMP (SR)  11 Other (specify)   
 12 None used (open hole)   
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot  3 Mill slot  5 Gauzed wrapped  8 Saw cut  11 None (open hole)   
 2 Louvered shutter  4 Key punched  6 Wire wrapped  9 Drilled holes   
 7 Torch cut  10 Other (specify)   
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 16 ft. to 40 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement  2 Cement grout  3 Bentonite  4 Other   
 Grout Intervals: From 4 ft. to 16 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank  4 Lateral lines  7 Pit privy  10 Livestock pens  14 Abandoned water well   
 2 Sewer lines  5 Cess pool  8 Sewage lagoon  11 Fuel storage  15 Oil well/Gas well   
 3 Watertight sewer lines  6 Seepage pit  9 Feedyard  12 Fertilizer storage  16 Other (specify below)   
 13 Insecticide storage   
 Direction from well? South How many feet? 50-60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Top soil			
5	16	sandy brown clay			
16	35	MED to fine grey & Red sand			
35	40	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-18-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/year) 3-18-92 under the business name of hUEA Water Well Drilling by (signature) Jalucha

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4