WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

DRIS							Topeka, Kansas 66620			
County			Fraction		Section number		Township number Range number			
1. Location of well:	NE	2.2	NW1/4 NW1/4 SW1/4		33		1 16 s	R 23	E.	
2. Distance and direc	tion from neares	t town or city: 3	milesen	ST 3. Own	er of well:	C	RAIC BIAG	KSDME		
Street address of well		. ANG I	RANSOM.		72					
4. Locate with "X" i		PARSE	Sketch map:	3,,	tate, zip c		6. Bore hole dia. 7 in Well depth 4 ft.	. Completion date _	79	
N	 ,	Owe.	•			ŀ	7 Cable tool X Rotary			
						Hollow rod Jetted Bored Reverse rotary				
				,		8. Use: X Domestic Public supply Industry Irrigation Air conditioning Stack				
₹ w x							Lawn (Oil field water C	Other	
Field,						9. Casing: Material PIASI Height: Above or below Threaded Selder & Surface				
							Threaded Verded Strace In. RMP PVC Weight Ibs./ft.			
S 1 Mile ————————————————————————————————————							Dia. 5 in. to 84 ft. de	pth Wall Thickness: in	nches or	
5. Type and colar of	material		,		From	То	Dia in. to ft. de	name 76.S.S	Ę	
		10 6	SANDRO	a K	0	42	Type plastic	1		
		· •		CA				Length	<u>′</u>	
	FI	Me SA	Nd & ClA	4	42	53	Set betweenft.	_ft. and	ft.	
Clay					53	78	Gravel pack? YES Size		- 5/8 11	
Shale				78	84	11. Static water level:		6/79		
							12. Pumping level below to			
							ft. after		g.p.m.	
			70		-		Estimated maximum yield		g.p.m.	
	المعدة الجرازية	FIG. Chi	RECK 75	2	_7	Ţ.	13. Water sample submitted Yes X No	: ma	o./day/yr.	
	ويعيباه متعدها بمعطولة فيقودي	Yd	13.8.1 -47	cattle.	r		17. Well head completion:			
	- Committee of the Comm	vc13	Yd		1 3 0	1 1	Pitless adapter	Inches abov	e grade	
	proper is provided for beinging to			et de	e ald	7	15. Well grouted?	Bentonite	_Concrete	
		vd J.				-	Deoth: From fr. 1	0 <u> </u>	h	
}	ing lighter to effect and agg part	And the second s	Section for the transfer and the compression of the first section of the section	menden anna Vinit . I	. 3	C 3 8 %	ft Direction _	ble contamination: 5	een	
	and the state of t	CONSTRUCTION OF THE PROPERTY AND ADDRESS.	TOTAL			A N	Well disinfected upon com	oletion? X Yes	h	
						2.814. m	. 97. Pump: Manufacturer's name	X Nat installed	¹ ~{ `	
100							Model number		/olts	
			7/100			-	Length of drop pipe	ft. capacity	—g.p.m. 🥞	
			Z4 10				Submersible	Turbi		
		/Uss a second	sheet if needed)39 1	/			Jet Centrifugal	Recij Othe	procating of	
18. Elevation:	19. Remarks:	(Ose a second	ما ما ما	L T.	La	.1	20. Water well contractor			
CONCRETE SIAD 10 BE							This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Tapography: INSTALLED by CUSTOMER						DEL. DRILLING 303				
- Hill AT ground level.						Business norme Adaress 368. Hill CTy. KS. L7642				
Slope Upland							Signed Authorized	epresentative	de-4+ 79	
Valley										