WATER WELL RECORD			Form WW	/C-5	Division of Wate	r Resources App. N	o. <u>105'1</u>	
1 LOCATION OF WATER WELL:			Fraction		Section Number	Township No.	Range Number	
County: Ness			SE 1/4 SW 1/4 SW		16	T 16 S	R 24 □E 🗸 W	
		Address of Well Location; i		Global Positioning				
from nearest town or intersection: If at owner's address, check here					Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
					Elevation:			
2 WATER WELL OWNER: Pete Flax					Collection Method:			
RR#, Street Address, Box #: RR1 Box 91				GPS unit (Make/Model:)				
City, State, ZIP Code : Ransom			ı, KS 67572		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL								
1	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 98 ft.							
SEC.	SECTION BOX: Depth(s) Groundwater Encountered (1).70 ft. (2) ft. (3) ft.							
ļ , ₁	WELL'S STATIC WATER LEVEL70ft. below land surface measured on mo/day/yr. 2/3/.11							
'		DOT VIDED 20	ft atter	hours puin	ping. Nu gpin			
W -NW - NE - EST. YIELD. 30gpm. Well water wasft. after							ft gpinggpin	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Irrigation Industrial Domestic-lawn & garden Monitoring well								
	<u> </u>	Was a chemical/	bacteriological sample s					
S If yes, mo/day/yr sample was submitted								
Water well disinfected? ✓ Yes ☐ No								
5 TYP	E OF CA	ASING USED: Steel	V PVC □ Ot	her				
CASIN	G JOIN	rs: 🗹 Glued 🔲 Clan	nped Welded] Threaded	[
Casing diameter .5 in. to .98 ft., Diameter in. to ft., Diameter in. to ft.								
Casin	g height	above land surface24	in., Weight	2.91	lbs./ft., Wall thic	kness or gauge N	o21	
TYPE OF SCREEN OR PERFORATION MATERIAL:								
Steel Stainless Steel PVC Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From98								
From								
6 GROUT MATERIAL: Neat cement Cement grout Pentonite Other								
Grout In		From .49 It. to	ft., From .	• • • • • • • • • • • • • • • • • • • •	ft. to ft.,	From	ft. toft.	
wnatis		est source of possible conta		Liventoelre	ona 🗀 Inggoticida	otomoro 🗀 Otl	(
Septic tank								
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
Direc	ction fro	n well		Distance	from well			
FROM	TO	LITHOLOG	IC LOG	FROM			JGGING INTERVALS	
0	14	Gumbo Clay						
14	35	Sand rock				***************************************		
35	40	Fine Sand						
40	50	Sand Rock						
50	62	Sand						
62	73	Sand rock						
73	88	sand						
88	93	Clay	· · · · · · · · · · · · · · · · · · ·					
93	98	Shale						
7 CONTRIA CTIONIC OR LANDOWNING CREPTUTICATIVO V. T								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .06/06/11 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No0199 This Water Well Record was completed on (mo/day/year) .06/28/11								
under the business name of Karst Water Well Drilling & Service, Inc. by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St. Suite 420, Topeka, Kansas 66612-1367								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								