
USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215



Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

County	Fraction	Section number		Township number	Range number	
1. Location of well: Jane	1/4 1/4	1/4 32	~~ ?	T 16 s	R 28	E/W
2. Distance and direction from nearest town or city: South Radd An 1 3. Owner of well: Robert Hanan						
The state of the s				Wills Kans 678 74		
4. Locate with "X" in section below:	Sketch map:			6. Bore hole dia, in. Well depth ft.	Completion date	444
N N				7 Cable tool Rotary Driven Dug		
				Hollow rod Jetted		rotary
W I I I I I I I I I I I I I I I I I I I				8. Use: Domestic A Public supply Industry		
E (/e/)				Irrigation Air conditioning Stock Lawn Oil field water Other		
SW SE Drue way &				9. Casing: Material Height: Above or below		
t				Threaded Welded Surface in.  RMP PVC Weight lbs./ft.		
				Dia. 5 in. to 07 ft. depth Wall Thickness: inches or		
5. Type and color of material	_	From	То	Dia in. to ft. dep		
Exercise Secretary 12 2	The property of the section of the s	and the second	ع	10. Screen: Manufacturer's r		
Cop sec				Type Dia. Slot/gauze Length 15		
Soubser	The second of th	7.	5	Set between	ft. and	ft.
Clay:	The second control of the second seco	5	14	Gravel pack? Size ra	5 .	<u></u>
Rocayelay.	The second secon	40 14	19	11. Static water level:ft, below land sur	. 14/4/	day/yr.
Charthon Sany Clay: 19 26			26	12 - Pumping level below land surfaces:  ft. after hrs. pumping g.p.m.		
Clay with the first			45	ft. after hrs. pumping g.p.m.		
d. J			58	Estimated maximum yield		
Tuth:		48 58	171	. **	Date	
sculver.			11	14. Well head completion:	18	
Dand fairly love			91	Pitless adapter Inches above grade 15. Well grouted? t.a		
Sand Harl.			96	With: Neat_cement Bentonite Concrete		
& Ovidle for the face			104	Depth: From 7 ft. to 5 ft.  16. Negrest source of possible contamination 7 ft.		
S A D & D			. 64	ft. 150 Direction Type		
pand to the my			108	Well disinfected upon comple	tion? Yes XNot installed	No R
Land Coose		108	128	Manufacturer's name	Verles.	290 IC
say stone		128	13 C	Model number 125	ft. capacity Valts	.p.m. 🗧
Skele		131		Type: Submersible	Turbine	
() Iso a so	cond sheet if needed)	25		Jet Centrifugal	Reciproco	iting 🔓 🕠
18. Elevation: 19. Remarks:	,			20. Water well contractor's of This well was drilled under m	certification:	"IN
				is true to the best of my know	•	- 12
Topography: Hill				Business name License No.		
Slope				Address Shalls Thems 57		
Upland Valley				Signed Washington Control Authorized rep	resentative Date	5 N
Forward the white hive and nink copies to the Denor	tment of Health and Environment				Form WWC-	