WATER WELL RECORD FORM WWC-5	Division of Water Resources App. No. 29/20259
1 LOCATION OF WATER WELL: Fraction Lane NW 1/4 NW 1	Section Number Township Number Range Number
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here \Boxed. Intersection of Hwy 23 & Road 240—NW corner	Global Positioning System (GPS) information: Latitude: N 38 37.641 (in decimal degrees) Longitude: W 100 30.281 (in decimal degrees) Elevation: 2810
2 WATER WELL OWNER RR#, St. Address, Box # City, State, ZIP Code Dean & Ruby Wilson 256 N Hwy 23 Dighton, KS 67839	Datum: ☑ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method: ☐ GPS unit (Make/Model: ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 160	ft.
Depth(s): Groundwater Encountered (1)	11. (2) $11. (3)$
N WELL'S STATIC WATER LEVEL	ft. below land surface measured on mo/day/yr
Pump test data: Well water was	ft. after hours pumping gpm
NW - NE - EST. YIELD gpm: Well water was	ft, after hours pumping gpm
WELL WATER TO BE USED AS: Public w	ater supply Geothermal Injection well
Domestic of Feedlot XOII field water supplementation of Industrial Domestic forms	ater supply
SW SE Irrigation Industrial Domestic-lawn & Was a cliemical/bacteriological sample submitted	o Department? Tives XI No
S If yes, no/day/yr sample was submitted	or repairment.
1 mile Water Well Disinfected? ⊠ Yes □ No	***************************************
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other	
CASING JOINTS: Glued Clamped Welded Thr	eaded
CASING JOINTS: \(\subseteq \text{Glued} \subseteq \text{Clumped} \subseteq \text{Uniform} \) Casing diameter \(\begin{array}{cccccccccccccccccccccccccccccccccccc	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)	
4 ² ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot	
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw	h cut
ISCREEN-PERFORATED INTERVASSE: From 120 fc to	160 ft Grom ft to
From ft. to	ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 20 ft. to	160 ft., From ft. to ft.
K CDOUT MATERIAL. [7] Note that the control of the	160 ft., From ft. to ft. 160 ft., From ft. to ft. 161 ft., From ft. to ft. 162 ft., From ft. to ft.
6 GROUT MATERIAL: ☐ Neat cement Cement grout Grout Intervals From 0 ft. to 20 ft. From	ft to ft From ft to ft
what is the hearest source of possible confamination:	TO WELL TO THE PROPERTY OF THE PARTY OF THE
	stock pens
or apply bernage tageon rate	storage
	nce from well
FROM TO LITHOLOGIC LOG FRO	
0 2 Surface	
2 32 Caliche w/sandy clay strks 32 140 Sandy clay w/caliche strks	
32 140 Sandy clay w/caliche strks 140 153 Fine & med sand w/caliche lenses	
153 160 Black shale	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or □ plugged	
under my jurisdiction and was completed on (mo/day/year) 4/5/12 And this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/year) 4-13-17	
Kansas Water Well Contractor's License No. 554 . This Water Well Record was completed on (mo/day/year) 4-13-12 under the business name of Woofter Pump & Well Inc. by (signature)	
INSTRUCTIONS: Please fill in blanks and check the correct answers. Send three copies (white blue pink) to kinese Department of Health and Environment Pursue of	
INSTRUCTIONS: Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to kansas Department of lealth and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.	

Check: ☐ White Copy, ☐ Blue Copy, ☐ Pink Copy