


1 LOCATION OF WATER WELL: County: SALINE 085 Fraction SW 1/4 NE 1/4 NW 1/4 Section Number 12 Township Number T 16 S Range Number R 3 SW

Distance and direction from nearest town or city street address of well if located within city?

in city limits

2 WATER WELL OWNER: CITY OF ASSARIA Water Well #3  
RR#, St. Address, Box #: CITY HALL Board of Agriculture, Division of Water Resources  
City, State, ZIP Code: ASSARIA, KS. Application Number: 2677

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 81 ft. ELEVATION: 20 ft.

Depth(s) Groundwater Encountered 1. 21 ft. 2. 20 ft. 3. 9-7-87 ft.

WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 9-7-87

Pump test data: Well water was 20 ft. after 20 hours pumping 20 gpm

Est. Yield 20 gpm: Well water was 20 ft. after 20 hours pumping 20 gpm

Bore Hole Diameter 20 in. to 20 ft., and 20 in. to 20 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes 20 No 20; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes 20 No 20

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 20 Clamped 20

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 20

2 PVC 4 ABS 7 Fiberglass Threaded 20

Blank casing diameter 20 in. to 20 ft., Dia. 20 in. to 20 ft., Dia. 20 in. to 20 ft.

Casing height above land surface 20 in., weight 20 lbs./ft. Wall thickness or gauge No. 20

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 20

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 20

SCREEN-PERFORATED INTERVALS: From 20 ft. to 20 ft., From 20 ft. to 20 ft.

From 20 ft. to 20 ft., From 20 ft. to 20 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 20 ft., From 20 ft. to 20 ft.

From 20 ft. to 20 ft., From 20 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 20

Grout Intervals: From 20 ft. to 20 ft., From 20 ft. to 20 ft., From 20 ft. to 20 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? N How many feet? 100

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

↓ Plugged according to state spec.

05 25-80 ft Chert/bedded SAND

20 0-25 ft CEMENT GROUT

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-7-87 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 9-10-87

under the business name of PETERSON IRRIGATION INC. by (signature) Mick Peterson

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.