

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Scott</u>	<u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$	<u>22</u>	T <u>16</u> S	R <u>31</u> EW

Distance and direction from nearest town or city street address of well if located within city?

6 miles North of Manning, Kansas2 WATER WELL OWNER: John Hrbek

RR#, St. Address, Box # :

Board of Agriculture, Division of Water Resources

City, State, ZIP Code :

Healy, Kansas 67850

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 173 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 121 ft. 2. ft. 3. ft.WELL'S STATIC WATER LEVEL 121 ft. below land surface measured on mo/day/yr 5/17/84

Na Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 9 in. to 173 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well StockwellWas a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued Clamped

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded

2 PVC

4 ABS

7 Fiberglass

Threaded.

Blank casing diameter 5 in. to 140 ft., Dia in. to ft., Dia in. to ft.Casing height above land surface. 12 in., weight 2.9 lbs./ft. Wall thickness or gauge No. 265

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 140 ft. to 173 ft., From ft. to ft., From ft. to ft.GRAVEL PACK INTERVALS: From 120 ft. to 173 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other Drill cuttingsGrout Intervals: From 15 ft. to 120 ft., From 4 ft. to 15 ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? EastHow many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	17	Clay	17	22	Gyp
22	29	Clay	29	30	Rock
30	38	Clay	38	44	Fine sand clay streaks
44	53	Sand	53	80	Fine sand clay streaks
80	125	Fine sand	125	150	Sand
150	152	Clay	152	160	Sand
160	167	Fine sand clay streaks	167	173	Yellow clay
173		Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/18/84 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 232 This Water Well Record was completed on (mo/day/yr) 5/23/84under the business name of Weishaar Drilling & Supply Inc. by (signature) Wayne Weishaar

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.