


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 33 Township Number T 16 S Range Number R 33 EW

Distance and direction from nearest town or city street address of well if located within city?
 2 1/4^M East + 9 3/4^M North of Scott City

2 WATER WELL OWNER: Lonnie Rohrbough
 RR#, St. Address, Box #: Rt. 3, Box 44-A
 City, State, ZIP Code: Scott City, KS. 67871
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 185' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 143' ft. 2. ... ft. 3. ... ft.
 WELL'S STATIC WATER LEVEL: 143' ft. below land surface measured on mo/day/yr 11/08/89.
 Pump test data: Well water was ... ft. after ... hours pumping ... gpm
 Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter: 10 in. to 185' ft., and ... in. to ... ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes ... No ; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded
 Blank casing diameter: 5 1/2 in. to 165' ft., Dia ... in. to ... ft., Dia ... in. to ... ft.
 Casing height above land surface: 18' in., weight ... SCH. 40 lbs./ft. Wall thickness or gauge No. ...
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From ... 165' ft. to ... 185' ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From ... 185' ft. to ... 20' ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other
 Grout Intervals: From ... ft. to ... ft., From ... 0 ft. to ... 20' ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? South How many feet? 2000'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Top Soil			
6	36	Sandy Clay			
36	45	Very Fine Sand			
45	54	Coarse Sand			
54	84	Sand Stone, Clay Streaks			
84	104	Sandy Clay, Medium Sand Streaks			
104	106	Hard Sand Stone			
106	132	Very Fine Sand			
132	138	Sandy Clay			
138	161	Very Fine Sand			
161	170	Coarse Sand, Small to Medium Gravel Loose			
170	183	Yellow Clay			
183	185	Shale			
185'		Total Depth of Well			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/29/89 and this record is true to the best of my knowledge and belief. Kansa Water Well Contractor's License No. KS.# 514 This Water Well Record was completed on (mo/day/yr) 11/30/89 under the business name of Miller Gearhead & Pump Repair INC. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.