WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | · · · · · · · · · · · · · · · · · · · | | | | | T | | |
|--|---|---------------------------|-----|----------------|--|--|--|----------|
| 1. Location of well: | County | Fraction | | Section number | | Township number Range number | | |
| 200357 (7 #811; | Wichita | SW 1/4 SE 1/4 SW | 1/4 | | 2 | T 16 S | R 35 | E.Ø |
| 2. Distance and direction from nearest town or city: 11N, 1½E of | | | | | | otto Harp | | |
| Street address of well location if in city: Marienthal, KS R.R. or s | | | | | treet: RFD #1 te, zip code: Marienthal, KS 67863 | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | i | 6. Bore hole dia 26 in Well depth 195 ft. | Completion date — | |
| , N | N . | | | | } | | | |
| | NE | L r | | | | 7 Cable tool Rotary Hollow rod Jetted | | e rotary |
| | E Xwell | 1/4 mi, | | | Ì | 8. Use: Domestic Po | | |
| Wille | * Xwell | ——> <u> </u> | Sep | tic/ | | | r conditioning Stoo | |
| sw | SE | • | | | ŀ | 9. Casing: Materia Stee | I field water Oth | |
| l lx | i | | | | | Threaded WeldedX | _ISurface 10 | in. |
| S 1 →1 Mile → | | | | | | RMPPVCWeight 31.67_lbs./ft. Dia 16_in. to 195ft. depth Wall Thickness; inches or | | |
| 5. Type and color of material | | | | | То | Dia in. to ft. dep | | 8 |
| | | | | | | 10. Screen: Manufacturer's r | | |
| Clay | | | | 0 | 28 | Type Prime Steel Dig. 16 in. | | |
| Sd rock | | | | 28 | 30 | | _ Length <u>40 ft</u> .ft. and <u>195</u> | |
| Clay | | | | 30 | 38 | ft. andft. | | |
| 3243 | | | |) | | Gravel pack? Gravel pack. Grave | | |
| Fine sd clay | | | | 38 | 46 | 142 ft. below land surface Date 7-23-75 | | |
| % Gyp | | | | • 46 | 51 | 12. Pumping level below land surfaces: 162 ft. after hrs. pumping 350 g.p.m. | | |
| Clay | | | | 51 | 63 | 165 ft. after 4 hrs. pumping 430 g.p.m. | | |
| Cd coerce by | | | | (2) | | Estimated maximum yield | | |
| Sd coarse | | | | 63 | 74 | Yes X No Date | | |
| Fine sd clay | | | | 74 | 80 | (4) Well head completion: | 12 Inches above g | ,] |
| Sd rock | | | | 80 | 86 | Pitless adapterInches above grade | | |
| Med sd | | | | 86 | 90 | With Name company Rentantian description Company | | |
| | | | | | | Depth: From ft. to | / / ft. | |
| Clay | | | | | 105 | 16. Negrest source of possible contamination: ft. 1320 Direction E Type Septic | | |
| Sd coarse | | | | 105 | 115 | 17 Pump. Net installed | | |
| Fine sd clay | | | | 115 | 170 | Manufacturer's name West | | ller " |
| Sd. correc | | | | 100 | 100 | Model number <u>IIS</u> Length of drop pipe <u>180</u> | 7.30 | 460_ |
| Sd coarse | | | | 170 | 183 | Туре: | | g.p.m. |
| | | | | 183 | 188 | Submersible Jet | X Turbine Reciproc | ating |
| Shale | (Use a second sh | eet if needed) | | 188 | 190 | Centrifugal | Other | Sec |
| 18. Elevation: | 19. Remarks: | | | | | 20. Water well contractor's of This well was drilled under m | | 1 |
| | | | | | | is true to the best of my know | ledge and belief. | · |
| Topography:Hill | | | | | | Weishaar Dril | | 32 |
| Slope | | | | | | Address Stott | ty KS 6787 | |
| Upland Valley | | | | | 4 | Authorized rep | resentative7_20-7 | - |
| | ue and pink copies to the Department of | of Health and Environment | | | <u>-</u> L | 1 | Form WWC | |