WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number Range number			
1. Location of	well: Wichita	SW 1/4 SW 1/4 S	E1/4	30		т 16 s	R 36	E.	
2. Distance and direction from nearest town or city: 10N, $1\frac{1}{2}E$ of 3. Own					l: 1	Willard Kalbach			
Street address of well location if in city: Leoti, KS R.R. or : City, sto					code:	Leoti, KS 67861			
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 26 in			
Suplice Suplice						Well depth 214 ft. 5-23-75			
	,	, F		_1		7 Cable tool Rotary Hollow rod Jetted			
1, mi. 7						8. Use: Domestic Public supply Industry			
					X Irrigation Air conditioning Stock Lawn Oil field water Other				
w - sw se E X					9. Casing: Materia Steel Height Abover below				
1 1 1 1						Threaded Welded XiSurface 10in.			
	S — 1 Mile ————————————————————————————————————					RMP	iWeight <u>t</u> th!Wall Thickness	: inches or	
5. Type and c	olor of material			From	То	Diain. to ft. dep	th gage No	.188	
						10. Screen: Manufacturer's n	name		
Clay	<i>†</i>			0	31	Prime Steel		in.	
Fine sd clay				31	35	Set between			
Gvr	u			35	63	ft. c		/4- 1 ft.	
						11. Static water level:		mo./day/yr.	
Sa c	coarse T			63	70	ft. below land sur			
Clay	7			70	78	12. Pumping level below land 168 ft. after 4	surfaces:	0	
Sd rock				78	80	189 ft. after 4 hrs. numping 900 g.p.m.			
Fine sd clay				80	9 0	Estimated maximum yieldg.p.m. 13. Water sample submitted:mo./day/yr.			
Tille St. Clay				00	102	Yes X No Date			
Clay				90	###	(14) Well head completion:	12		
Sd coarse				107	112	Pitless adapter Inches above grade			
Clay				112	122	With: Neat cement Bentonite Concrete			
						Depth: From ft. to ft. 16. Neorest source of possible contamination:			
Sd coarse				122	129	ft. 2640 Mection NE Type Septic			
Fine sd clay				129	140	Well disinfected upon comple			U
Sd coarse				140	158	17. Pump: Manufacturer's name (425)		Roller	~ 0
	Fine sd good			158	191	Model number	_ HP _ 60	00 4160	(3)
Sd coarse					Type:	_ 11. capacity c _	l	a.	
Sa (CONT 26			191	200	Submersible Jet	X_ Tur	bine ciprocating	L
Clay	(Use a second s	heet if needed)		200	202	Centrifugal	OH		i W
18. Elevations				202	211	20. Water well contractor's o		this recent	10
	Yello Shale			211 213	213 215	This well was drilled under m is true to the best of my know			t
Topography:	5.16.20				~~)	Weishaar Dr	illing	232 License No.	۶الإ
Slope						Address Address	tv. Ks 6	Licelise Ido.	غ ا ک
Upland						Signal Authorized ran	fesentative 7-1)	1/4 1/4 1/4 1/4
L variey					44		Form	27 /0	Z I U