## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County Fraction		Section	n number	Township number Range number										
1. Location of well:	Wichita	NW 1/4 SW 1/4 SE 11N, ½E, ½N	1/4	24	т 16 s	R 37	E.								
2. Distance and dire	ction from nearest town or city:	3. Owner of we	ılı. Jo	oe Zellner Jr.											
5				tate, zip code: Marienthal, KS 67863											
4. Locate with "X" in section below: Sketch map:				6. Bore hole dia. 26 in . Completion date											
N					Well depth _203 ft.										
NW NE /2 mc.					Hollow rod Jetted Bored X Reverse rotary										
E W Loptie XW				) [	8. Use: Domestic Public supply Industry										
S W SW SE S					Irrigation Air conditioning Stock Lawn Oil field water Other     9. Casing: Material Steel   Height: Above or below     Threaded Welded X   Surface 10   in .     RMP PVC   Weight 31 67   lbs ./ft .										
								ı ←				<del></del>	Dia. 16 in. to 203ft. de	pth Wall Thickness: in	ches or
								5. Type and color of material				То	10. Screen: Manufacturer's		
Clay				37	Free Flo										
Fine sd clay				40	Slavgauze 125	_ Length 40 f	1								
			37		Set between										
Gyp			40	58	Gravel pack? Yes Size re		<del>-1</del>								
Sd med			58	64	11. Static water level:  134 ft. below land su		./day/yr. 21-74								
Clay			64	78	12. Pumping level below lan	d surfaces:									
Fine sd clay				87	165 ft. after 4 hrs. pumping 1300 g.p.m.										
Clay				105	Estimated maximum yield										
				1.	Yes X No	Date	/ddy/yr.								
Fine sd clay				120	(4.) Vell head completion: Pitless adapter	12 Inches above	crode								
Sd coarse				127	(15) Well grouted?										
Fine sd clay				162	With: Neat cement Bentonite Concrete Depth: From ft. to Off.										
Sd coarse				176	16. Negrest source of possible contamination: ft. 2640 Direction Type Septic										
G2I-				100	Well disinfected upon completion? Yes No.										
Sd rock				178	17. Pump:	Not installed									
Fine sd clay				182	Manufacturer's name Lavne & Bowler  Model number HP 100 vol. 60										
Sd coarse			182	201	Length of drop pipe 190	)_ ft. capacity <u>140</u>	2 <b>0</b> .p.m. (								
Yellow			201	210	Type: Submersible	X Turbine	,								
Shale	(Use a second s	heet if needed)	210		Jet Centrifugal	Recipro	cating S								
18. Elevation:	19. Remarks:				20. Water well contractor's	certification:									
					This well was drilled under no is true to the best of my know		report								
Topography:					Weishaar Dril	ling 2	232_ ≨								
Slope					Address Scott C	Ky. KS 6787	ense No.								
Upland Valley				k	Signed Authorized re	pesentative 7-19									
	e and pink copies to the Department	of Health and Environment		1		Forpt WW	1								