


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 25 Township Number T 16 S Range Number R 37 E/W
 County: Wichita

Distance and direction from nearest town or city street address of well if located within city?
 9 1/2 miles north Leoti, Ks.

2 WATER WELL OWNER: Jack Gorsuch
 RR#, St. Address, Box # : Rt. 2 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Leoti, Ks. 67861 Application Number: 15259

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 215 ft. ELEVATION: 3335
 Depth(s) Groundwater Encountered 1. 155 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 155 ft. below land surface measured on mo/day/yr 9-15-93
 Pump test data: Well water was 210 ft. after 6 hours pumping 550 gpm
 Est. Yield 550 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 26 in. to 215 ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 16 in. to 175 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. SDR26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 175 ft. to 215 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 215 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 20 ft. to 3 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? 150 How many feet? south

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	16	top soil & sandy clay	213	215	yellow clay
16	32	sandy clay	217	229	shale
32	49	sandy clay & little cliche 1' (hard)			
49	65	cliche & little clay			
65	82	sand & little clay			
82	98	sandy clay			
98	114	sand & gravel & little clay			
114	132	sand & clay streaks			
132	147	sand & gravel & little clay (tight)			
147	164	sand (fine to medium) & little clay			
164	175	sand (med. to coarse) 11'			
175	180	cemented sand (hard) 5'			
180	196	sand (medium) 16'			
196	208	sand (medium to coarse) 12'			
208	213	yellow clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-25-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 473 This Water Well Record was completed on (mo/day/yr) 10-10-93 under the business name of Tyler Water Well by (signature) *[Signature]*

OFFICE USE ONLY
T
R
E/W
SEC.
1/4
1/4
1/4