

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: <div>County: Greeley</div> <div>Fraction: NE 1/4NW 1/4SE 1/4</div> <div>Section number: 6</div> <div>Township number: T 16</div> <div>Range number: S R 39</div> <div>E/W: E/W</div>			
2. Distance and direction from nearest town or city: 16 mi. north, 1/2 mi. east, 1/2 south, & 1/8 mi east Street address of well location if in city:		3. Owner of well: Heye Wilken R.R. or street: City, state, zip code: Leoti, Kans. 67861	
4. Locate with "X" in section below: <div><div>1 Mile</div><div><div>N</div><div>W</div><div>E</div><div>S</div><div>1 Mile</div></div><div><div>NW</div><div>NE</div><div>SW</div><div>SE</div></div></div>		Sketch map: <div><div>20'</div><div>X</div><div>20'</div></div>	
5. Type and color of material		6. Bore hole dia. 26 in. Completion date 12-22-75 Well depth 202 ft.	
Top soil, clay & little lime		7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary	
Sand & clay streaked		8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other	
Sand		9. Casing: Material STEEL Height: Above or Below Threaded Welded X Surface 12 in. RMP PVC Weight 40 lbs./ft. Dia. 16 in. to 152 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 219	
Clay		X Screen: Manufacturer's name W. A. Brown	
Sand (cemented) & 2" Clay		Type Free Flo Dia. 16	
Clay		Slot/gauze slot Length X 250"	
Shale		Set between X 152 ft. and X 202 ft. ft. and ft.	
		Gravel pack? yes Size range of material 5/8	
		11. Static water level: 140 ft. below land surface Date 12-25-75	
		12. Pumping level below land surfaces: 160 ft. after 4 hrs. pumping 1300 g.p.m.	
		ft. after hrs. pumping g.p.m.	
		Estimated maximum yield 2000 g.p.m.	
		13. Water sample submitted: mo./day/yr.	
		Yes X No Date	
		14. Well head completion: Pitless adapter 18 Inches above grade	
		15. Well grouted? yes	
		With: Neat cement X Bentonite Concrete	
		Depth: From 0 ft. to 10 ft.	
		16. Nearest source of possible contamination: None	
		ft. Direction Type	
		Well disinfected upon completion? Yes X No	
		17. Pump: Not installed	
		Manufacturer's name Layne	
		Model number 79502 HP 100 Volts 440	
		Length of drop pipe 180 ft. capacity 1200 g.p.m.	
		Type:	
		Submersible X Turbine	
		Jet Reciprocating	
		Centrifugal Other	
18. Elevation:		19. Remarks:	
Topography:		Level ground	
Hill			
Slope			
X Upland			
Valley			
		20. Water well contractor's certification:	
		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
		ARK VALLEY PUMP & SUPPLY 123	
		Business name Box 235 Holla, Colo.	
		Address	
		Signed W. Smith Date 2/9/76	
		Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

$$\frac{1}{T} \frac{6}{39} \frac{E}{W} \frac{6}{\text{Sec}} \frac{NE}{1/4} \frac{USE}{1/4}$$