


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County GREELY	Xraction NE 1/4 SW 1/4 SE 1/4	Section number 13	Township number T 16 S	Range number R 42 E/W																														
2. Distance and direction from nearest town or city: 13 North of Tribune on Hiway 27, 8 1/2 West, 1/4 North 1/8 West Street address of well location if in city: West				3. Owner of well: V.M. Young R.R. or street: Tribune, Ks. 67879 City, state, zip code:																																
X Locate with "X" in section below: N W E S 1 Mile Sketch map: 				6. Bore hole dia. 26 in. Completion date 2-21-76 Well depth 248 ft.																																
5. Type and color of material <table border="1"><thead><tr><th></th><th>From</th><th>To</th></tr></thead><tbody><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td></tr></tbody></table>					From	To																												7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
					From	To																														
8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																				
X Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.4 lbs./ft. Dia. 16 in. to 249 ft. depth Wall Thickness: inches Dia. 16 in. to 249 ft. depth gage No. 1219																																				
10. Screen: Manufacturer's name Johnson Division Type Galv. Dia. 16" Slot/gauze 100 Length 20' Set between 218 ft. and 238 ft. Perf. 198-218 ft. and 238-248 ft. Gravel pack? yes Size range of material 1/8" Down																																				
11. Static water level: 185 ft. below land surface Date 1-20-76 mo./day/yr.																																				
12. Pumping level below land surfaces: 229 ft. after 3 hrs. pumping 625 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 600 g.p.m.																																				
13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date 1-20-76 mo./day/yr.																																				
14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade																																				
15. Well grouted? YES With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																																				
16. Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																				
Pump: <input type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																				
18. Elevation:		19. Remarks: Well Surges after 229' Customer Furnished own Pump		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling 208 Business Phone Box A Garden City, Mo. Address Signed Mark Stetson Date 6-29-76 Authorized representative																																

16 420 13 NESUSE
T R W E
1/4 1/4 1/4

The
Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Industrial
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67843

V. M. YOUNG
Greeley County
12-9-75

Location: SE 13-16-42
13 miles North of Tribune on hiway 27, 8½ miles
West, ¼ North, 1/8 West

Static Water Level - 170'

0	2	Top Soil
2	9	Brown Clay
9	17	Fine Sand & Clay
17	31	Brown Clay & White Rock (Hard)
31	46	Fine to Med. Sand & Gravel
46	64	Brown Clay
64	76	Fine to Med. Sand & Gravel
76	93	Brown Clay & White Rock
93	101	Fine to Med. Sand (10% Clay)
101	109	Brown Clay
109	134	Fine to Med. Sand & Fine Gravel (10% Clay)
134	140	Fine to Med. Sand & White Rock (20% Clay)
140	171	Fine to Med. Sand & Gravel
171	198	Brown Sandy Clay
198	238	Fine to Med. Sand & Gravel
238	242	Yellow Clay
242	245	Shale

T.D. 248'