


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NW 1/4 Section Number 25 Township Number T 16 S Range Number R 42 E/W

County: Greeley Distance and direction from nearest town or city street address of well if located within city?
8 n, 8 w, 4 n, 1/2 w of Tribune, KS 67879

2 WATER WELL OWNER: Larry Steele Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Rt 1 Box 91 Application Number: 19678
City, State, ZIP Code: Tribune KS 67879

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 240 ft. ELEVATION: 3775

Depth(s) Groundwater Encountered 1. 202 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 202 ft. below land surface measured on mo/day/yr 6-5-98
Pump test data: Well water was not tested ft. after by us. hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 26 in. to 240 ft., and in. to ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter 16 in. to 200 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. SDR26
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 200 ft. to 240 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 25 ft. to 240 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 25 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? west How many feet? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	16	top soil & clay	239	246	shale
16	32	sandy clay			
32	49	clay & cliche 2' very hard			
49	65	clay & sand mix			
65	82	sand & cemented sand			
82	114	sand & little clay			
114	132	sand medium & 2' clay			
132	180	sandy clay & cliche			
180	192	sand medium			
192	196	clay			
196	209	sandy clay			
209	224	sand medium to course			
224	226	clay			
226	233	sand medium to course			
233	239	yellow clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-25-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 473 This Water Well Record was completed on (mo/day/yr) 6-25-98 under the business name of Tyler Water Well Service Inc by signature [Signature]

OFFICE USE ONLY
T
R
EW
SEC
1/4
1/4
1/4