


1 LOCATION OF WATER WELL: County: Ellsworth Fraction: SW 1/4 SW 1/4 SE 1/4 Section Number: 21 Township Number: T 16 S Range Number: R 6W E/W

Distance and direction from nearest town or city street address of well if located within city?  
1/4 mile north of east end Kanopolis Reservoir

2 WATER WELL OWNER: ~~Treas Grideratta shop~~ Shirley A Treas  
 RR#, St. Address, Box #: 312 West Crawford Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Salina Kans. 67401 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 21.3 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 21.3 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ND ft. after 1.5 hours pumping 2 gpm  
 Est. Yield 2 gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 6 in. to 43 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes  No  If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes  No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 4 in. to 21 ft., Dia. in. to ft., Dia. in. to ft.  
 Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. SAR R6  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 21 ft. to 24 ft., From ft. to ft.  
 From 37 ft. to 38 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 13 ft. to 43 ft., From ft. to ft.  
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 3 ft. to 13 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination: ND  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	1	Sand, silty			
1	23.5	Gravel + sand arkosic kiawa:			
23.5	25	Shale, yellow			
25	37	Shale, dark gray			
37	37.5	Sandstone, fine			
37.5	43	Shale, dark gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/16/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 126 This Water Well Record was completed on (mo/day/yr) 9/7/84 under the business name of Hydraulic Drilling Co by (signature) O. J. Faust

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY