

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ellsworth		near 1/4 center 1/4 SW 1/4	35	T 16 S	R 6 E/W
Distance and direction from nearest town or city street address of well if located within city? 4 miles North & 6 miles West of Marquette, KS					
2 WATER WELL OWNER: Chris N. Hoffman III					
RR#, St. Address, Box # : P.O. Box 288			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Lindsborg, KS 67456			Application Number: 43,618		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 7/6/99 Pump test data: Well water was 42 ft. after 2 hours pumping 250 gpm Est. Yield 250 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter .20 in. to .48 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ☒ Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
☒ PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter 10 in. to 28 ft., Dia		7 Fiberglass	Threaded		
Casing height above land surface 12 in., weight 8.878 lbs./ft. Wall thickness or gauge No. .413					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		☒ Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS:		From 28 ft. to 48 ft.	7 Torch cut	10 Other (specify)	
GRAVEL PACK INTERVALS:		From 20 ft. to 48 ft.			
6 GROUT MATERIAL:					
1 Neat cement		☒ Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination: None within 1/4 mile					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	19	Gray Clay			
19	26	Fine Sand with Clay Streaks			
26	46	Medium to Coarse Sand			
46	48	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/12/99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 7/20/99 under the business name of PETERSON IRRIGATION, INC. by signature Mike Peterson					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					