

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Ellsworth		SW ¼ SE ¼ SE ¼		21		T 16 S		R 6 X/W	
Distance and direction from nearest town or city street address of well if located within city?									
Venago Area, Kanopolis Lake									
2 WATER WELL OWNER: Jim Robinson									
RR#, St. Address, Box # : 3660 S. Gilda									
City, State, ZIP Code : Wichita, KS 67215									
Board of Agriculture, Division of Water Resources									
Application Number: N/A									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 7 ft. below land surface measured on mo/day/yr 3/20/98							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield 5-10 gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 9 in. to 50 ft., and in. to ft.							
WELL WATER TO BE USED AS:									
☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes. No. ☒ ; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes ☒ No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded.									
Blank casing diameter 5 in. to 10 ft., Dia. 5 in. to 45 ft., Dia. in. to ft.									
Casing height above land surface 12 in., weight 2.37 lbs./ft. Wall thickness or gauge No. 214									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From 45 ft. to 50 ft.									
GRAVEL PACK INTERVALS: From 20 ft. to 50 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite 4 Other									
Grout Intervals: From 0 ft. to ft., From 20 ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank ☒ Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? Southwest How many feet? 200									
FROM		TO		LITHOLOGIC LOG		FROM		TO	
0		1		Topsoil, Sandy					
1		15		Medium To Coarse Gravel, Tan					
15		27		Hard Sandstone, Tan					
27		50		Blue Shale w/some Sandstone streaks					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/20/98 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 3/23/98									
under the business name of Peterson Irrigation, Inc. by (signature) <i>Michael Peterson</i>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4