

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ellsworth		SE ¼ SE ¼ NW ¼	16	T 16 S	R 8W E/W
Distance and direction from nearest town or city street address of well if located within city? 4½ S of Ellsworth, Kansas					
2 WATER WELL OWNER: Kelly Wacker RR#, St. Address, Box # : 1545 Avenue O City, State, ZIP Code : Ellsworth, Kansas 67439 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION: Unknown			
N 1 Mile W E S		Depth(s) Groundwater Encountered 1. 60 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 60 ft. below land surface measured on mo/day/yr 4/12/96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 10 gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 7 7/8 in. to 125 ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded		Threaded			
2 PVC 4 ABS 7 Fiberglass		Blank casing diameter 5 in. to 85 ft., Dia 12 in. to 2.8 ft., Dia in. to ft.			
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch. 40		TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 85 ft. to 125 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 125 ft. From ft. to ft. From ft. to ft. From ft. to ft.		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.		What is the nearest source of possible contamination:			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage			
Direction from well? North		How many feet? 250			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil			
3	50	Shale			
50	125	Sand rock			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/12/96 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 4/17/96 under the business name of Kelly's Water Well Service, Inc. by (signature) Kevin Good					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4